



PRODUCT SPECIFICATIONS

TECHNICAL DATA



MA AXIAL FAN



DESCRIPTION

Axial extract MA fans with automatic shutters.
Designed for through the wall or wall mount application.
Air performance tested as per HVI standards.
Certified by ETL and conforms to UL & ULC electrical safety standards.

Five year warranty.

CASING

Durable plastic housing constructed of ETL recognized, UV protected thermoplastic resin (flame rating - 5VA).

MOTOR


Sleeve bearing motor ensures quiet operation and designed for operation up to 20,000 hours. Suitable for air stream temperature from 34 °F to 113 °F.

SUITABLE FOR:

Bathroom / Living Area

DIMENSIONS

Model	Measurements [ins]				
	B	H	L	D	L1
100	6 1/2"	5 7/8"	3 5/8"	3 7/8"	1 1/4"
125	7 1/2"	6 13/16"	3 7/8"	4 15/16"	1 5/16"
150	8 3/8"	7 11/16"	4 1/2"	5 7/8"	1 5/16"



* The parameters RPM, Watts, Amps are indicated at 0.03 in.WG static pressure.

Tel: 888-640-0925
513-348-3853
Fax: 513-268-4597

Sales@ventsus.com
VentsUS.com
11013 Kenwood Road,
Cincinnati, Ohio 45242



2013-03



MA

PRODUCT SPECIFICATIONS

TECHNICAL DATA

AXIAL FAN

PERFORMANCE

AMCA International Licensed Products

Model	RPM*	Sones	Duct Dia	Watts*	Amps*	CFM vs. Static Pressure (Ps) in WG		Max Ps	Volts
						0"	0.03"		
100 MA	2756	1.82	4"	17	0.18	44	37	0.17	120 / 60 Hz

AMCA International Non-Licensed Products

Model	RPM*	Sones	Duct Dia	Watts*	Amps*	CFM vs. Static Pressure (Ps) In. WG		Max.Ps	Volts
						0"	0.03"		
125 MA	2150	2.6	5"	19.2	0.21	102	90	0.18	120 / 60 Hz
150 MA	2130	2.7	6"	35.2	0.4	176	158	0.196	120 / 60 Hz

MODEL	QUANTITY	COMMENTS	PROJECT
			location:
			architect:
			engineer:
			contractor:
			submitted by:

Tel: 888-640-0925
513-348-3853
Fax: 513-268-4597

Sales@ventsus.com
VentsUS.com
11013 Kenwood Road,
Cincinnati, Ohio 45242



2013-03