

# prestige

## Fully Condensing Water Boiler



# TriangleTube

## Engineering Submittal

### Prestige Solo 399 HP



#### TriMax Control System

- Graphical display with 6 navigation buttons
- EZ Setup allows quick and easy boiler settings adjustment
- Logging function records sensor readings for system optimization and troubleshooting
- Lockout screen includes a text description with basic troubleshooting information
- Outdoor temperature reset to maximize efficiency
- Two space heating call inputs with independent outdoor reset curves
- Domestic hot water priority with optional time-out
- Integrated cascade control for up to 6 Prestige boilers
- 0-10 VDC Modulation input
- Modbus building management system (BMS) interface
- Warm weather shutdown option
- Optional boiler freeze protection
- Capability to control up to 4 circulators
  - Central heating (CH) circulator
  - Domestic hot water (DHW) circulator
  - Auxiliary boiler circulator
  - System circulator

#### Prestige Solo Features

- Light weight construction for wall mounting
- Approved for zero clearance to combustibles
- 4" PVC, CPVC, PP, or AL29-4C venting up to 100 equivalent feet.
- Limited 10 year warranty on heat exchanger

#### Approvals

- 95.1% Thermal Efficiency
- ANSI Z21.13 and CSA 4.9 Boiler Standards Compliance
- ASME Boiler Certification – ASME “H” Stamp
- Low NOx operation exceeding SCQMD 2012 regulations


#### Stainless Steel Fire Tube Heat Exchanger

- 439 Stainless Steel heat exchanger construction
- Low pressure drop minimizes circulator size
- High water content provides stable temperature control
- Self cleaning flue ways reduce maintenance
- Suitable for use with propylene glycol up to 50% concentration

#### Standard Equipment


- Stainless steel premix burner
- Direct spark ignition with variable speed blower
- Full modulation from 25% to rated input
- Automatic air vent
- ASME 45 PSI pressure relief valve (optional PTRLV03 80 PSI available)
- Integrated pressure and temperature gauge
- Outdoor temperature sensor
- Automatic low water cutoff feature
- High temperature limit safety control
- Line voltage terminal strip with individual fuses
- Low voltage terminal strip with removable jumpers for manual or automatic reset limits
- Swing down control panel for easy access and servicing
- Alarm contact
- Polypropylene condensate pan and internal flue pipe
- Polypropylene vent/air connections with test ports

Project / Location: _____	Date: _____
Consulting Engineer / Architect: _____	
Mechanical Contractor: _____	
Notes: _____	



Model	Fuel	Input Modulation (MBH)	Thermal Efficiency %	Heating Capacity MBH	Net I=B=R	Boiler Water Volume (gal)	Supply Return Connection	Gas Connection	Vent/Air Diameter	Weight Lbs
PT399	Natural or Propane Gas	112 - 399	95.1	379	330	7	1 1/2"	1"	4"	200

### Pressure Drop Curve with Grundfos Circulators



Delta T	GPM	Available System Head (Feet)		
		UP26-99F	UP26-116F	UP43/50-75F
20	37.9	---	---	4.0
30	25.3	10.0	16.0	13.0
40	19.0	16.0	21.0	18.0