

10K, 12K, 14K BTU THRU-THE-WALL AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24 hour timer
- Auto restart function
- Slide-out filter access



FOLLOW ME
Portable remote control thermostat feature for total room coverage



NON-ENERGY STAR

	3PATWH10002 w/ electric heater	3PATWH12002 w/ electric heater	3PATWH14002 w/ electric heater
UPC CODE	8-42149-02417-8	8-42149-02418-5	8-42149-02419-2
COOLING CAPACITY (Btu)	10,000/9,800	12,000/11,700	14,000/13,600
HEATING CAPACITY (Btu)	10,600/8,600	10,600/8,600	10,600/8,600
COVERAGE (sq. ft.)	400–450	450–550	550–700
EER	9.6	9.5	9.3/9.5
ENERGY STAR RATED	No	No	No
FAN SPEEDS (Cool/Fan/Heat)	3/3/1	3/3/1	3/3/1
AMPS (Cool)	4.6/5.0	5.5/5.9	6.9/7.5
AMPS (Heat)	15.0/13.5	15.0/13.5	15/13.5
WATTS (Cool)	1,042/1,021	1,263/1,232	1,505/1,431
WATTS (Heat)	3,450/2,821	3,450/2,821	3,450/2,821
DECIBELS (Hi/Mi/Lo)	57/55/53	61/59/57	61/60/59
INTERIOR TRIM KIT INCLUDED	Yes	Yes	Yes
FITS STANDARD WALL SLEEVES	Yes (sold separately)	Yes (sold separately)	Yes (sold separately)
UNIT DIMENSIONS (WxHxD) (in.)	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/2}	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/2}	24 ^{1/4} x 14 ^{1/2} x 20 ^{1/2}
PKG. DIMENSIONS (WxHxD) (in.)	28 x 17 x 26 ^{3/4}	28 x 17 x 26 ^{3/4}	28 x 17 x 26 ^{3/4}
STUFFING QTY. (20'/40'/40' HQ)	120/255/306	120/255/306	120/255/306
WEIGHT (Net/Gross) (lbs.)	69/80	78/89	78/89
REFRIGERATION	R410A	R410A	R410A
OUTLET CONFIGURATION	20 AMP 230V	20 AMP 230V	20 AMP 230V

THRU-THE-WALL AIR CONDITIONER SLEEVE

- Fits all standard 24 in. thru-the-wall AC units
- Minimize heat loss & reduce outdoor noise transmissions into the room
- Quality galvanized steel construction with a durable painted finish
- Easily adjustable: includes adjustable mounting brackets & locking clips
- Weather safe: protects unit with weather-tight seal
- Contains front and rear cover panels to seal the sleeve when unit is removed



PAWS1 thru-the-wall air conditioner sleeve	
UPC CODE	8-42149-02312-6
UNIT DIMENSIONS (WxHxD) (in.)	25 ^{1/2} x 15 ^{1/4} x 17 ^{1/2}
PKG. DIMENSIONS (WxHxD) (in.)	28 x 3 ^{1/4} x 20
WEIGHT (Net/Gross) (lbs.)	24/25

THRU-THE-WALL ACs WITH ELECTRIC HEATER