



COMMERCIAL DEHUMIDIFIER

250 PINT MODELS



| | 1PACD250 |
|---|----------------------------------|
| UPC | 8-42149-02610-3 |
| WATER REMOVAL CAPACITY (90°F, 90% RH) | 250 pts./Day (31.25 gal./Day) |
| WATER REMOVAL CAPACITY (80°F, 60% RH) | 142 pts./Day (17.75 gal./Day) |
| POWER SUPPLY | 15AMP 115V |
| RATED POWER (W) | 1180 |
| RATED CURRENT (A) | 10.4 |
| DEFROST TYPE | Hot Gas Bypass |
| TIMER (hr.) | 1-24 |
| OPERATING TEMPERATURE | 33°F – 100°F |
| REFRIGERANT | R410A |
| WEIGHT (Net/Gross) (lbs.) | 137/147 |
| PRODUCT SIZE (WxHxD) (in.) | 21 x 38 x 22 |
| PACKAGE SIZE (WxHxD) (in.) | 23 ^{13/16} x 40 x 25 |
| DRAIN HOSE LENGTH (ft.) | 40 |
| WASHABLE AIR FILTER | Yes |

COMMERCIAL APPLICATIONS

- Manufacturing, printing, or packing/shipping facility
- Warehouses and records/media storage rooms
- Indoor pools, health clubs, and gymnasiums
- Hospitals & pharmaceutical labs
- Temporary office or school trailers
- Computer rooms
- Supermarkets, restaurants and bakery
- Large plants (water treatment, power, etc.)
- Museums, libraries, and art galleries
- Large basement or attic
- Any area affected by humidity from flooding, water leakage, or natural disasters
- Green houses



5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us