



AIR CONDITIONER

10,000 BTU WINDOW AC



WINDOW AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24 hour timer
- Window mounting kit
- Auto restart function
- Tilt-out filter access

CHOOSING THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM

1 MEASURE AREA OF THE ROOM

CALCULATE ROOM SIZE
room length x room width = sq. ft.

2 MATCH ROOM SIZE WITH CORRECT BTUs

ROOM SIZE (sq. ft.)	BTUs	
150	10' x 15'	5,000
250	15.5' x 16'	6,000
350	17.5' x 20'	8,000
450	18' x 25'	10,000
550	22' x 25'	12,000
700	25' x 28'	15,000
1,000	31.25' x 32'	18,000
1,500	37.5' x 40'	25,000
2,000	40' x 50'	28,500

3 CONFIRM WINDOW OPENING SIZE

MEASURE WINDOW OPENING IN INCHES
for thru-the-wall units, confirm & measure wall opening size in inches

4 CHECK ELECTRICAL REQUIREMENTS

OUTLET CONFIGURATIONS

15A-115V

15A-230V

20A-230V

30A-230V

DETERMINE IF YOUR CIRCUIT IS ADEQUATE

1PEC10000	
UPC CODE	8-42149-02688-2
COOLING CAPACITY (BTU)	10,000
COVERAGE (sq. ft.)	450–550
EER	3.52
ENERGY STAR RATED	Yes
FAN SPEEDS (Cool/Fan)	3/3
AMPS	7.5
WATTS	833
DECIBELS (Hi/Mi/Lo)	59/57/54
WINDOW WIDTH (Min./Max.) (in.)	22 ^{1/2} /36 ^{3/4}
WINDOW HEIGHT (Min.) (in.)	14 ^{3/4}
UNIT DIMENSIONS (WxHxD) (in.)	19 x 14 x 21
PKG. DIMENSIONS (WxHxD) (in.)	23 x 17 x 25
STUFFING QTY. (20'/40'/40' HQ)	180/380/456
WEIGHT (Net/Gross) (lbs.)	75/80
REFRIGERATION	R410A
OUTLET CONFIGURATION	 15 AMP 115V



PA/SS_1PEC10000/07212017