



AIR CONDITIONER

12,000 BTU WINDOW AC



WINDOW AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24 hour timer
- Window mounting kit
- Auto restart function
- Tilt-out filter access

CHOOSING THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM

1 MEASURE AREA OF THE ROOM

CALCULATE ROOM SIZE
room length x room width = sq. ft.

2 MATCH ROOM SIZE WITH CORRECT BTUs

ROOM SIZE (sq. ft.)	BTUs	
150	10' x 15'	5,000
250	15.5' x 16'	6,000
350	17.5' x 20'	8,000
450	18' x 25'	10,000
550	22' x 25'	12,000
700	25' x 28'	15,000
1,000	31.25' x 32'	18,000
1,500	37.5' x 40'	25,000
2,000	40' x 50'	28,500

3 CONFIRM WINDOW OPENING SIZE

MEASURE WINDOW OPENING IN INCHES
for thru-the-wall units, confirm & measure wall opening size in inches

4 CHECK ELECTRICAL REQUIREMENTS

OUTLET CONFIGURATIONS

DETERMINE IF YOUR CIRCUIT IS ADEQUATE

1PEC12000	
UPC CODE	8-42149-02689-9
COOLING CAPACITY (BTU)	12,000
COVERAGE (sq. ft.)	450–550
EER	3.52
ENERGY STAR RATED	Yes
FAN SPEEDS (Cool/Fan)	3/3
AMPS	9.0
WATTS	1,000
DECIBELS (Hi/Mi/Lo)	59/57/54
WINDOW WIDTH (Min./Max.) (in.)	28 ^{1/8} /41 ^{3/4}
WINDOW HEIGHT (Min.) (in.)	18 ^{3/4}
UNIT DIMENSIONS (WxHxD) (in.)	25 ^{1/2} x 17 ^{3/4} x 23 ^{3/4}
PKG. DIMENSIONS (WxHxD) (in.)	30 ^{1/2} x 20 ^{1/4} x 26 ^{1/4}
STUFFING QTY. (20'/40'/40' HQ)	96/216/267
WEIGHT (Net/Gross) (lbs.)	110/128
REFRIGERATION	R410A
OUTLET CONFIGURATION	15 AMP 115V



PA/SS_1PEC12000/11292017

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us