



# DEHUMIDIFIER

## 50 PINT EJECTOR PUMP



### DEHUMIDIFIER FEATURES

- Easy access bucket with handle
- Bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Water level window
- Side exhaust
- Built-in pump
- Optional continuous 6 foot drainage

	1PEDP50
<b>UPC CODE</b>	8-42149-02636-3
<b>CAPACITY (pts./Day)</b>	50
<b>COVERAGE (sq. ft.)</b>	3,000
<b>EER</b>	2.0
<b>ENERGY STAR RATED</b>	Yes
<b>FAN SPEEDS</b>	2
<b>AMPS</b>	4.7
<b>WATTS</b>	535
<b>DECIBELS (Hi/Lo)</b>	54/53
<b>BUCKET CAPACITY (pts.)</b>	18.8
<b>UNIT DIMENSIONS (WxHxD) (in.)</b>	15 <sup>1/2</sup> x 23 <sup>3/4</sup> x 11 <sup>1/4</sup>
<b>PKG. DIMENSIONS (WxHxD) (in.)</b>	16 <sup>3/4</sup> x 24 <sup>1/4</sup> x 12 <sup>1/2</sup>
<b>STUFFING QTY (20'/40'/40' HQ)</b>	303/624/832
<b>WEIGHT (Net/Gross) (lbs.)</b>	38/41
<b>MIN. OPERATING TEMP</b>	41°F
<b>REFRIGERATION</b>	R410A
<b>OUTLET CONFIGURATION</b>	 15 AMP 115V



PA/SS\_1PEDP50/05302017

5401 Dansher Road  
Countryside, IL 60525

866.996.9255  
630.323.2301

www.perfectaire.us  
support@perfectaire.us



# DEHUMIDIFIER


## 50 PINT



**BUCKET W/ HANDLE**



**WASHABLE FILTER**




**ELECTRONIC CONTROLS**



### DEHUMIDIFIER FEATURES

- Direct-to-drain hose access
- Easy access bucket with handle
- Bucket full indicator
- Adjustable humidistat
- Washable filter
- Automatic defrost control
- Auto shut-off/restart
- Timer function
- Water level window
- Comfort option: Unit controls humidity based on room temperature
- Side exhaust
- Check filter light

	4PAD50
<b>UPC CODE</b>	8-42149-02639-4
<b>CAPACITY</b> (pts./Day)	50
<b>COVERAGE</b> (sq. ft.)	3,000
<b>EER</b>	2.0
<b>ENERGY STAR RATED</b>	Yes
<b>FAN SPEEDS</b>	2
<b>AMPS</b>	4.7
<b>WATTS</b>	495
<b>DECIBELS</b> (Hi/Lo)	55/54
<b>BUCKET CAPACITY</b> (pts.)	12.7
<b>UNIT DIMENSIONS</b> (WxHxD) (in.)	15 <sup>1/2</sup> x 23 <sup>1/4</sup> x 11
<b>PKG. DIMENSIONS</b> (WxHxD) (in.)	16 <sup>3/4</sup> x 25 <sup>1/4</sup> x 12 <sup>1/4</sup>
<b>STUFFING QTY</b> (20'/40'/40' HQ)	303/624/832
<b>WEIGHT</b> (Net/Gross) (lbs.)	36/39
<b>MIN. OPERATING TEMP</b>	41°F
<b>REFRIGERATION</b>	R410A
<b>OUTLET CONFIGURATION</b>	 15 AMP 115V



PA/SS\_4PAD50/05302017

5401 Dansher Road  
Countryside, IL 60525

866.996.9255  
630.323.2301

[www.perfectaire.us](http://www.perfectaire.us)  
[support@perfectaire.us](mailto:support@perfectaire.us)