

Air Circulators

Direct Drive High Velocity Fans

Efficient air cooling for almost any kind of indoor/outdoor location. The TP fans produce air circulation that will keep an area from becoming stagnant with hot or polluted air. This fan is ideal for manufacturing areas, furnace rooms, welding booths, warehouses, drilling rigs, stockyards etc.

- Standard sizes are 24", 30", 36" and 42" diameter
- CFM ranges from 5,420 to 28,791
- High efficient Air Foil cast aluminum blades
- All-welded, all-steel construction
- Heavy gauge, expanded metal safety guards
- Coated with polyester powder coat paint system for long life and superior corrosion resistance
- 2" female pipe threaded bushing for quick mounting to wall, ceiling or pedestal base



SIZE	HP	RPM	CFM	VELOCITY AT FAN FPM	AIR PROJECTION 300 FPM* AT NO.FT	APPROX. SHIPPING WEIGHT
TP-24	1/2	1140	5420	1700	30	85
	3/4	1140	6579	2100	40	105
	1-1/2	1750	8320	2650	70	125
TP-30	1/2	860	7518	1550	40	150
	3/4	860	9062	1850	50	160
	1	1140	9966	2050	60	170
	2	1140	12012	2500	70	200
	3	1750	15300	3100	80	250
	3/4	860	12003	1700	40	218
TP-36	1	860	15046	2150	50	230
	2	1150	16050	2300	60	240
	3	1150	19700	2900	70	260
	5	1150	21370	3100	90	300
	2	860	19892	2050	80	360
	5	860	26600	2750	110	460
	5	1150	28791	3000	120	380

