

30CFO-SWDS-3-Q

30CFO-SWDS-3-Q

Product Description

Increase productivity and improve work area safety with high performance Schaefer washdown duty air circulators. Designed to withstand frequent washing and for long life in wet and moist environments these fans are ideal for food and beverage processing facilities, kitchens, hospitals and other clean, corrosive or humid environments.

Features

Choice of three sizes: 20", 24" and 30" diameter

Corrosion resistant electro-polished 304 stainless steel, OSHA compliant guards

Extremely high airflow compared to competitive offerings

Pedestals and stainless steel wall mounts available

Made in the USA



Specifications

Air Velocity (@ 10')	TBD
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	10760
Rpm 60 Hz Motor	1000-1200
Drive	Direct
Enclosure	TENV
Phase	3
Speeds	1
Cord	Not included
Diameter (inches)	30
Frequency (hz)	60/50
Guard Color	Metallic

Insulation Class	F
Nameplate Amps	2.0/1.0
Number Of Wings	3
Bore Size (inches)	5/8
Power (hp)	1/2
Product Net Weight (lbs)	55
Performance Test #	1102
Voltage	208-230/460
Blade Material	Stainless Steel
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	Metallic
Product Shipping Dimensions (in)	34 x 34 x 20

Blade Pitch (degrees)	18
Cfm Range (free Air)	10001 - 15000
Distinguishing Feature	Washdown Duty
Fixed Or Portable	Fixed
Guard Material	Stainless Steel
Mount Type Recommended	SS Wall Mounts
Oscillating	No
Rpm 50 Hz Motor	800-1000
Sound Level (dda @ 10')	73
Thermal Protection	No
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA

**Speed Control
Compatible?**

No