

36DF-3

36DF-3

Product Description

Direct flow circulation fans feature very high airflow with a narrow airflow pattern to deliver high volumes of fast moving air to cool cows and other animals. Ships fully assembled, available unassembled for high packing density and low shipping cost.

Features

Powerful ½ hp motor provides high airflow with a narrow airflow pattern for very high air speeds and effective cooling

Thermally protected TEAO motors with matching blades for high performance and long life

Safety spaced steel guards dipped in zinc and powder coated for superior corrosion resistance

Easy open guards for cleaning and/or blade replacement

19" T-shaped, powder coated steel, fan mount included

Single speed and direct drive

Two year warranty

Made in the USA



Specifications

Blade Color	Gray
Brand	Schaefer
Cfm (free Air)	12970
Rpm 60 Hz Motor	800-900
Drive	Direct
Enclosure	TEAO
Frame Size	48YZ
Mount Included	VS36FMT
Phase	3
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	25.9
Cord	Not included

Diameter (inches)	36
Frequency (hz)	60/50
Guard Color	White
Mount Type Included	Ceiling
Nameplate Amps	2.3/1.2
Number Of Wings	3
Bess Lab Performance Test #	8057
Power (hp)	1/2
Product Net Weight (lbs)	60
Voltage	230/460
Maximum Rpm	825

Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White
Product Shipping Dimensions (in)	41 x 41 x 18
Speed Control Compatible?	No
Cfm Range (free Air)	10001 - 15000
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Product Shipping Dimensions(cm)	41 x 41 x 18 Inches

Air Velocity (@ 5 Times Diameter)	960
Blade Material	Galvanized Steel

Rpm 50 Hz Motor	700-800
Country Of Origin	US
Guard Spacing (inches)	1/2 - 1 UL507