


FRD Series

Inline Mixed Flow Rectangular Fans



STANDARD FEATURES

- Hinged door for service access
- Airflow up to 2318 cfm
- Permanently lubricated sealed ball bearings
- 100% speed controllable
- Automatic reset thermal overload protection
- Airstream temperatures up to 140°F
- Prewired electrical box
- Three-year factory warranty

Model	A	B	C	D	Metal Gauge	Weight
FRD 12-6	11 7/8	5 7/8	15 3/4	11	20	17
FRD 16-8	15 3/4	7 3/4	19 3/4	15	20	30
FRD 16-8XL	15 3/4	7 3/4	19 3/4	15	20	30
FRD 24-14	23 3/8	13 3/4	28 1/2	20	20	86



Systemair Inc. certifies that the FRD Series shown herein is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and AMCA Publication 311 and complies with the requirements of the AMCA Certified Ratings Program.

All dimensions in inches. Weights in pounds.

Line	Qty	Fan Specifications					Motor Specifications				
		Model No.	Tag	CFM	SP	Fan RPM	Watts	Volts	Phase	Hertz	Encl
1											
2											
3											
4											

Accessory Items	1	2	3	4	Accessory Items	1	2	3	4

Project: _____ Submitted: _____
 Customer: _____ Approved: _____
 Location: _____