

485B2G-LT

485B2G-LT

Product Description

Maintain a safe and productive work environment by exchanging hot or contaminated air using Schaefer low cost galvanized, box exhaust fans. These low cost, high volume exhaust fans are protected from the elements with outlet side aluminum shutters and mount in walls of almost any thickness, typically with the outlet shutter flush, or nearly flush with the outside wall. Fans ship fully assembled with aluminum inlet shutters, self-adjusting belt tensioner and galvanized outlet guard.

Features

G90 galvanized construction, for corrosion resistance and long life

Totally enclosed, thermally protected motors for safety and long life

Easy belt replacement, minimal maintenance required

Remote Lubrication System optional

Suitable for buildings with any wall thickness

Available in 36" or 48" sizes

3-wing or 5-wing blade style

Two year warranty

Made in the USA



Specifications

Air Velocity (@ 10')	TBD
Blade Color	Gray
Brand	Schaefer
Cfm (free Air)	20500
Drive	Belt
Enclosure	TEAO
Housing Material	Galvanized Steel
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	55" X 55"

Cord	Not included
Diameter (inches)	48
Frequency (hz)	60
Guard Color	Metallic
Nameplate Amps	9.5
Number Of Wings	5
Operating Temperature (low) F	TBD
Power (hp)	2
Product Dimensions (L X W X H Inches)	TBD

Blade Material	Galvanized Steel
Product Color	Metallic
Speed Control Compatible?	No
Able To Ship Small Parcel	No
Cfm Range (free Air)	20001 - 30000
Fixed Or Portable	Fixed
Guard Material	Galvanized Steel
Oscillating	No
Country Of Origin	US

Speeds	1
Vfd Compatible	No

Product Net Weight (lbs)	TBD
Voltage	230
Air Velocity (@ 5 Times Diameter)	TBD

Guard Spacing (inches)	1 - 2
Housing Color	Gray