

485S112

485S112

Product Description

Schaefer slant wall exhaust fans are the first choice of growers and other building owners looking for very low cost, high volume exhaust fans that flush-mount from inside the building and shed water and snow, once installed. Designed for high airflow and high efficiency and available in many sizes and configurations to meet application requirements. Fans ship fully assembled with aluminum inlet shutters, self-adjusting belt tensioner (on belt-drive models) and galvanized outlet guard.

Features

G90 galvanized construction, for corrosion resistance

Totally enclosed, thermally protected motors for safety and long life

Easy belt replacement, minimal maintenance required

Suitable for buildings with up to 6" wall thickness using standard rough-in dimensions.

Available in belt drive or direct drive

Two year warranty

Made in the USA



Specifications

Blade Color	Gray
Brand	Schaefer
Cfm (free Air)	24000
Drive	Belt
Housing Material	Galvanized Steel
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	55" x 55-3/4"
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	TBD
Cord	Not included

Guard Color	Metallic
Nameplate Amps	6.8-6.4
Number Of Wings	5
Bess Lab Performance Test #	13544
Cfm (medium)	TBD
Operating Temperature (low) F	TBD
Power (hp)	1 1/2
Product Net Weight (lbs)	250
Voltage	208-230
Blade Material	Galvanized Steel
Cfm (high)	TBD

Able To Ship Small Parcel	No
Cfm Range (free Air)	20001 - 30000
Fixed Or Portable	Fixed
Guard Material	Galvanized Steel
Oscillating	No
Country Of Origin	US
Guard Spacing (inches)	1 - 2
Housing Color	Gray
Cfm/watt (@0.10")	13.9
Cfm (@ 0.10")	21800
Cfm/watt (@0.05")	15.2

Diameter (inches)	48
Frequency (hz)	60

Product Color	Metallic
Product Shipping Dimensions (in)	35 x 63 x 67
Speed Control Compatible?	No

Cfm (@0.05")	23100
--------------	-------