

The brand new premium line of commercial heat recovery air handling units for ceiling mounting with the high-efficient rotary heat exchanger. Provides 883 CFM air flow capacity. Optionally accomplished with no heater (RP series), electric heater (RP-HE series) or water heater (RP-HW series) and ready for operation with all necessary control elements.

FANS

High-efficient EC fans, backward-curved, external rotor. Low power consumption at any speed, low noise level and stable operation in any climate conditions.

CONTROL

The integrated plug-and-play controls on the basis of the Carel kVent controller. Easy connecting via web-interface using the Ethernet-Modbus and BACnet.

PLUG FAN CASING

The casing panels are made of steel with zinc-aluminium coating and internally lined with 1^{9/16}" heat- and sound-insulating mineral wool layer. The unit has C4 corrosion resistance class in compliance with ISO 12944. Each model is available in left- and right-handed modifications. The unit has service access on both sides and on the bottom.

HEAT EXCHANGER

High-efficient aluminum rotary heat exchanger.

CONTROL PANELS

- A30 th-Tune: standard control panel with handy interface ensures basic setup of parameters.
- A32 pGDe: control panel with expanded functionality ensures complete setup of parameters.

FILTERS

Washable MERV13, MERV8 (optional) panel filters in exhaust and supply air streams.





BYPASS AND DAMPERS

Integrated automatic external dampers with Belimo actuators.



DIMENSIONS

Measurements [in]							
L	W	H	H1	S	S1	E1	E1
55 1/8"	55 3/4"	24 3/4"	11 3/4"	19 3/4"	19 7/8"	14 1/8"	6 3/4"



TECHNICAL DATA

Model		RP 1500
Nominal airflow [CFM]		883
EC fans	Phase/voltage [50/60Hz/VAC]	~1.200/277
	Power/current [kW/A]	2x0.46/3.0
	Fan speed [min^{-1}]	2848
	Permissible ambient temperature [$^{\circ}\text{F}$]	-31...+122
	Motor protection	IP54
	Insulation class	F
	Motor sound power level to outlet [Sones]	24
	SFP @ nominal airflow, max. pressure [kW/(m^3/s)]	2x1.1
Filter class exhaust/supply standard (optional)		MERV13 (MERV8)/MERV13 (MERV8)
Weight (net, without packaging) [lb]		600
Protection class		IP34
Sound pressure level @ 1 ft to environment [Sones]		2.5


Sound power Lw in dB

Environment	66	65	62	52	33	53	48	51	59
Outlet	68	69	70	68	65	64	61	58	71
Hz	63	125	250	500	1000	2000	4000	8000	LwA

MODEL	QUANTITY	COMMENTS	PROJECT
			location:
			architect:
			engineer:
			contractor:
			submitted by: