

CR18K6E-TF5
HCFC, R-22, 60 Hz, 3 - Phase, 220/230 V [. Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	2.01
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):	
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	10.23
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.65
Capacity (BTU/hr)	17600	23600	Overall Height (in):	13.12
Power (W):	1645	1305	Mounting Length (in):	7.50
Current (Amps):	5.15	4.45	Mounting Width (in):	7.50
EER(BTU/Wh):	10.7	18	Mounting Height (in):	13.49
Mass Flow (lbs/hr):	258	304	Suction Size (in),Type:	3 / 4 Stub
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	77 Avg	81 Max	Initial Oil Charge (oz):	45
Vibration mils(peak-peak):	1.6 Avg	2.6 Max	Oil Recharge (oz):	43
Record Date:	2014-03-06		Oil Type:	POE
			Net Weight (lbs):	61.0
			Internal Free Volume (in^3):	
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	49.0	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	8.5					
Max Operating Current (Amps):						
RLA, MCC/1.4(use for contactor selection)(Amps):	6.1					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	5.4					
RPM:						
Box IP :						
UL File No:						
UL File Date:	1984-12-28					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	200/240	3	50	Air Conditioning
R-407C HFC	200/240	3	50	Air Conditioning
R-407C HFC	220/230	3	60	Air Conditioning