



FFM363G12DD-3V

FFM363G12DD-3V

Product Description

Schaefer fiberglass exhaust fans are designed and built to be highly efficient (high cfm/watt), long lived and competitively priced fans for agricultural and other applications. The fiberglass exhaust fans are used worldwide to exhaust high volumes of air from factories, warehouses, garages and other locations, where building owners value low capital cost and low operating cost. Fans ship fully assembled with aluminum inlet shutters, self-adjusting belt tensioner and powder coated outlet guard.

Features

Totally enclosed, thermally protected motors for safety and long life

Easy belt replacement, minimal maintenance required

Remote Lubrication System optional

Aluminum inlet shutter and powder coated outlet guard

Suitable for buildings with up to 12" wall thickness

Available in 36", 48" and 52" sizes

1-phase and 3-phase motors of various sizes

15 year housing warranty

Two year warranty

Made in the USA



Specifications

Blade Color	Gray
Brand	Schaefer
Cfm (free Air)	TBD
Rpm 60 Hz Motor	800-900
Drive	Direct
Enclosure	TEAO
Frame Size	48
Housing Material	Fiberglass
Phase	3
Rough-in Dimensions	43 1/2" x 43 3/4"

Diameter (inches)	36
Frequency (hz)	60/50
Guard Color	Black
Nameplate Amps	2.8/1.4
Number Of Wings	3
Power (hp)	1/2 / 1/3
Product Dimensions (L X W X H Inches)	TBD
Product Net Weight (lbs)	TBD
Voltage	208-230/460

Cfm Range (free Air)	5001 - 10000
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Rpm 50 Hz Motor	600-700
Country Of Origin	US
Guard Spacing (inches)	1 - 2
Housing Color	White

Speeds	1
Vfd Compatible	Yes
Cfm/watt (free Air)	TBD
Cord	Not included

Air Velocity (@ 5 Times Diameter)	TBD
Blade Material	Galvanized Steel
Cfm (high)	TBD
Product Color	White
Speed Control Compatible?	No

Cfm/watt (@0.10")	TBD
Maximum Static Pressure (in. H2o)	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	TBD
Cfm (@0.05")	9320