

ITEM # FTXM12WVJU9, FTXM-V SERIES

- Wall Mounted unit using R-32 Refrigerant (may not be available in your area - check local codes regarding sale and installation).
- Built-in Wi-Fi to control the system with the Daikin Comfort Control App
- Hybrid Cooling technology controls humidity efficiently even in low cooling loads and maintains dehumidification effect after the target temperature is reached.
- CLEAN function dries the interior of the indoor unit to reduce the amount of condensation present.
- The indoor unit has been re-

+ [more](#)



[Specifications](#) | [Electrical Data](#) | [Dimensions](#)

Specifications

Rated Capacity (Min. - Max.) - Cooling	12000 (4800 - 16000) Btu/h
Rated Capacity (Min. - Max.) - Heating	13600 (4800 - 22600) Btu/h
Power Consumption Rated - Cooling	909 W
Power Consumption Rated - Heating	906 W
Power Factor - Cooling	96.3 - 96.2 %
Power Factor - Heating	96.8 - 96.8 %
SEER2 / HSPF2 - Cooling	25.20
SEER2 / HSPF2 - Heating	10.70
EER2 Rated	13.20 Btu/h-W
COP2 Rated	4.40 W/W

Amount of Additional Charge of Refrigerant	0.22 oz/ft 20 g/m
Front Panel Color	White (N-9.5)
Airflow Rate (H) - Cooling	558 ft ³ /min 15.8 m ³ /min
Airflow Rate (H) - Heating	558 ft ³ /min 15.8 m ³ /min
Airflow Rate (M) - Cooling	395 ft ³ /min 11.2 m ³ /min
Airflow Rate (M) - Heating	413 ft ³ /min 11.7 m ³ /min
Airflow Rate (L) - Cooling	293 ft ³ /min 8.3 m ³ /min
Airflow Rate (L) - Heating	339 ft ³ /min 9.6 m ³ /min
Airflow Rate (SL) - Cooling	226 ft ³ /min 6.4 m ³ /min
Airflow Rate (SL) - Heating	254 ft ³ /min 7.2 m ³ /min
Fan Type	Cross Flow Fan
Fan Speed	5 Steps, Quiet, Auto
Heat Exchanger Type	Multi Slit Fin
Heat Exchanger - Rows x Stages	1 × 4 1 × 8 2 × 18
Heat Exchanger - Fin per Inch	18
Sound Pressure Level (H) - Cooling	45 dBA
Sound Pressure Level (H) - Heating	45 dBA
Sound Pressure Level (M) - Cooling	37 dBA
Sound Pressure Level (M) - Heating	39 dBA
Sound Pressure Level (L) - Cooling	29 dBA

Sound Pressure Level (L) - Heating	32 dBA
------------------------------------	--------

Sound Pressure Level (SL) - Cooling	23 dBA
-------------------------------------	--------

Sound Pressure Level (SL) - Heating	26 dBA
-------------------------------------	--------

Weight	29 lb 13 kg
--------	----------------

Gross Weight	38 lb 17 kg
--------------	----------------

Electrical Data

Voltage	208 to 230 V
---------	--------------

Frequency	60 Hz
-----------	-------

Number of Phases	1
------------------	---

Min. Circuit Ampacity	12.3 A
-----------------------	--------

Max. Fuse Ampacity	15 A
--------------------	------

Rated Load Amps	12.00 A
-----------------	---------

Outdoor Fan Motor - Rated Output	0.05 hp 37 W
----------------------------------	-----------------

Outdoor Fan Motor - Full Load Amps	0.31 A
------------------------------------	--------

Indoor Fan Motor - Rated Output	0.04 hp 27 W
---------------------------------	-----------------

Indoor Fan Motor - Full Load Amps	0.25 A
-----------------------------------	--------

Dimensions

Depth	10-13/16 in 275 mm
-------	-----------------------

Width	36-1/4 in 920 mm
-------	---------------------

Height	11-3/4 in 299 mm
--------	---------------------

Packaged Depth	15-3/8 in 391 mm
Packaged Width	39-3/4 in 1010 mm
Packaged Height	14-15/16 in 380 mm
Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	3/8 in 9.5 mm
Pipe Connections - Drain	5/8 in 16.0 mm
Max. Interunit Piping Length	82-1/64 in 25 m
Max. Interunit Height Difference	65-5/8 in 20 m
Chargeless	49.2 in 15 m