

ITEM # FTXM18WVJU9, FTXM-V SERIES

- Wall Mounted unit using R-32 Refrigerant (may not be available in your area - check local codes regarding sale and installation).
- Built-in Wi-Fi to control the system with the Daikin Comfort Control App
- Hybrid Cooling technology controls humidity efficiently even in low cooling loads and maintains dehumidification effect after the target temperature is reached.
- CLEAN function dries the interior of the indoor unit to reduce the amount of condensation present.
- The indoor unit has been re-

+ [more](#)



[Specifications](#) | [Electrical Data](#) | [Dimensions](#)

Specifications

Rated Capacity (Min. - Max.) - Cooling	18000 (9000 - 22000) Btu/h
Rated Capacity (Min. - Max.) - Heating	21600 (9000 - 30200) Btu/h
Power Consumption Rated - Cooling	1440 W
Power Consumption Rated - Heating	1665 W
Power Factor - Cooling	95.5 - 95.4 %
Power Factor - Heating	97.6 - 97.6 %
SEER2 / HSPF2 - Cooling	22.70
SEER2 / HSPF2 - Heating	10.00
EER2 Rated	12.50 Btu/h-W
COP2 Rated	3.60 W/W

Amount of Additional Charge of Refrigerant	0.22 oz/ft 20 g/m
Front Panel Color	White (N-9.5)
Airflow Rate (H) - Cooling	777 ft ³ /min 22.0 m ³ /min
Airflow Rate (H) - Heating	777 ft ³ /min 22.0 m ³ /min
Airflow Rate (M) - Cooling	583 ft ³ /min 16.5 m ³ /min
Airflow Rate (M) - Heating	558 ft ³ /min 15.8 m ³ /min
Airflow Rate (L) - Cooling	484 ft ³ /min 13.7 m ³ /min
Airflow Rate (L) - Heating	466 ft ³ /min 13.2 m ³ /min
Airflow Rate (SL) - Cooling	427 ft ³ /min 12.1 m ³ /min
Airflow Rate (SL) - Heating	413 ft ³ /min 11.7 m ³ /min
Fan Type	Cross Flow Fan
Fan Speed	5 Steps, Quiet, Auto
Heat Exchanger Type	Multi Slit Fin
Heat Exchanger - Rows x Stages	1 × 4 1 × 8 2 × 18
Heat Exchanger - Fin per Inch	18
Sound Pressure Level (H) - Cooling	49 dBA
Sound Pressure Level (H) - Heating	49 dBA
Sound Pressure Level (M) - Cooling	41 dBA
Sound Pressure Level (M) - Heating	40 dBA
Sound Pressure Level (L) - Cooling	36 dBA

Sound Pressure Level (L) - Heating	35 dBA
------------------------------------	--------

Sound Pressure Level (SL) - Cooling	33 dBA
-------------------------------------	--------

Sound Pressure Level (SL) - Heating	32 dBA
-------------------------------------	--------

Weight	33 lb 15 kg
--------	----------------

Gross Weight	46 lb 21 kg
--------------	----------------

Electrical Data

Voltage	208 to 230 V
---------	--------------

Frequency	60 Hz
-----------	-------

Number of Phases	1
------------------	---

Min. Circuit Ampacity	18.8 A
-----------------------	--------

Max. Fuse Ampacity	20 A
--------------------	------

Rated Load Amps	18.25 A
-----------------	---------

Outdoor Fan Motor - Rated Output	0.16 hp 123 W
----------------------------------	------------------

Outdoor Fan Motor - Full Load Amps	0.58 A
------------------------------------	--------

Indoor Fan Motor - Rated Output	0.08 hp 61 W
---------------------------------	-----------------

Indoor Fan Motor - Full Load Amps	0.46 A
-----------------------------------	--------

Dimensions

Depth	10-13/16 in 275 mm
-------	-----------------------

Width	43-5/16 in 1100 mm
-------	-----------------------

Height	11-3/4 in 299 mm
--------	---------------------

Packaged Depth	15-1/2 in 393 mm
Packaged Width	47-11/16 in 1212 mm
Packaged Height	15-13/16 in 401 mm
Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	1/2 in 12.7 mm
Pipe Connections - Drain	5/8 in 16.0 mm
Max. Interunit Piping Length	98-1/2 in 30 m
Max. Interunit Height Difference	82-1/64 in 25 m
Chargeless	49.2 in 15 m