

SUBMITTAL DATA

FLR24HP230V1R32AH
24000 BTU/H Floor Ceiling Heat Pump System

Job Name	Location	Date
Purchaser	Engineer	
Submmited to	For	
Unit Designation	Schedule No.	
  		
YBE1FB5F	FLR24HP230V1R32AH	XE72-44/E

GENERAL FEATURES

- AHRI Certificate: [215415517 \(Vireo R32\)](#), [215415520 \(Envo R32\)](#), [215415447 \(Sapphire R32\)](#)
- Quiet Operation and Multi-Speed Fan
- Floor Stand or Ceiling Mount
- Multi-Directional Air Flow
- Wireless Remote with LCD Display Included
- XE72-44/E Wired Controller Included
- Low Ambient Cooling and Heating
- (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested
- New R32 Refrigerant with Refrigerant Sensor

SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

SYSTEM TYPE			HEAT PUMP			FEATURES & FUNCTIONS SUMMARY	
Indoor Model			FLR24HP230V1R32AH			Inverter Type	G20
Outdoor Model			VIR24HP230V1R32AO	ENV24HP230V1R32AO	SAP24HP230V1R32AO	Ultra Low Frequency Torque Control	Yes
SYSTEM PERFORMANCE						Power Factor Correction	Yes
Cooling Capacity	Min - Max	Btu/h	11,957 - 30,316	11,957 - 30,316	13,003 - 32,966	Compressor Type - Inverter	High Efficiency Rotary
	Capacity @95°F	Btu/h	22,000	22,000	22,000	Basepan With Electric Heater	Yes
Heating Capacity	Min - Max	Btu/h	13,267 - 32,781	13,267 - 32,781	14,754 - 36,455	Indoor & Outdoor Fin Coating (Blue Fin)	Yes
	Capacity @47°F	Btu/h	24,000	24,000	24,000	Intelligent Defrosting	Yes
	Capacity @17°F	Btu/h	20,000	20,000	20,000	Intelligent Preheating	Yes
	Capacity @5°F	Btu/h	20,000	20,000	21,000	Low Voltage Startup	Yes
SEER2			22.5	22.5	23.0	Memory/Power Failure Recovery	Yes
EER2			12.6	12.6	13.0	Self Diagnosis	Yes
HSPF2			9.5	9.5	9.5	Wired Controller Interface	Yes
COP @5°F			1.80	1.80	1.80	WiFi Included	No
Cooling Temperature Range		*F	-20 - 122			Indoor Fan Type	Centrifugal
Heating Temperature Range		*F	-22 - 86			Multi Fan Speeds	4 Speeds
Refrigerant Type			R32			Indoor Unit Display	Yes
INDOOR UNIT			FLR24HP230V1R32AH			Auxiliary Electrical Heater	No
Air flow (Min-Max)		CFM	424 - 559			Ventilation (Outdoor Air)	No
Sound Pressure Level (Min - Max)		dB(A)	26 - 38			REMOTE CONTROLLER FUNCTIONS	
Dehumidification		pt/hr	5.28			Auto Mode	Yes
External Dimensions (L x D x H)		in	47-1/4 x 9-1/4 x 26-3/16			Auto Fan	Yes
Package Dimension (L x W x H)		in	53-11/16 x 30-5/16 x 11-13/16			Auto Swing (Horizontal Auto Swing)	No
Net Weight		lbs	72.8			Auto Swing - 180° (Vertical Auto Swing)	Yes
Gross Weight		lbs	88.2			Clock	Yes
OUTDOOR UNIT			VIR24HP230V1R32AO	ENV24HP230V1R32AO	SAP24HP230V1R32AO	Dry Mode	Yes
Sound Pressure Level		dB(A)	58	61	62	Dry Anti-Mildew (X-Fan) Mode	Yes
External Dimensions (L x D x H)		in	37-23/32 x 15-53/64 x 25-63/64	39-3/8 x 16-13/16 x 29-3/8	39-3/8 x 16-13/16 x 29-3/8	Energy Saving Mode	Yes
Package Dimension (L x W x H)		in	40-5/8 x 17-61/64 x 29-1/64	42-33/64 x 19-1/64 x 31-57/64	42-33/64 x 19-1/64 x 31-57/64	Dirty Filter Alert	No
Net Weight		lbs	92.6	103.6	115.8	Fan Speed Control (7 Speeds)	Yes
Gross Weight		lbs	102.5	114.7	126.8	I Feel Function	Yes
REFRIGERANT PIPING						Privacy Lock	Yes
Refrigerant Charge - R32		oz	42.3	49.4	56.4	Quiet Mode	Yes
Additional Charge		oz/ft	0.4	0.4	0.4	Room Temperature Display	No
Line Set Sized by Indoor Unit (Liquid - Gas)		in	1/4 - 5/8			Sleep Mode	Yes
Line Set Size (Liquid - Gas) - Flared Connections		in	1/4 - 5/8	1/4 - 5/8	1/4 - 5/8	3 Sleep Mode Options	Yes
Pre-Charge Length		ft	25			Timer Mode	Yes
Pipe Length (Min - Max)		ft	10 - 131	10 - 131	10 - 131	Turbo Mode	Yes
Max. Pipe Elevation		ft	82	82	82	Display On/Off Control	Yes
ELECTRICAL						Freeze Guard Mode	Yes
Power Supply			208-230V / 1Ph / 60Hz (Powered by the Outdoor Unit)			Power Failure Mode	Yes
Voltage Range (Min - Max)		VAC	187 - 253				
Rated Current - Cooling		A	13	5.9	14		
Rated Current - Heating		A	15.5	7.8	21.5		
MCA		A	22	11	25		
MOCP		A	30	15	40		
Suggested Breaker Size		A	25	15	25		
Main Power Wire Size		AWG	Per Local Code				
Interconnecting Wire Size		AWG	14 / 4				


NOTE:
Please check the Multi-zone submittals for Non-Ducted or Mixed Performance table.

DIMENSIONS

INDOOR UNIT

Unit: inch


FLR24HP230V1R32AH	
DIMENSIONS	
A	47 1/4
B	9 1/4
C	44 61/64
D	12 17/32
H	26 3/16



OUTDOOR UNIT

Unit: inch

VIR24HP230V1R32AO	
DIMENSIONS	
A	35
B	37 23/32
C	25 63/64
D	13 25/64
E	15 53/64
F	22 7/16
G	14 39/64
ENV24HP230V1R32AO	
DIMENSIONS	
A	36 11/32
B	39 3/8
C	29 3/8
D	14 17/32
E	16 13/16
F	24 1/64
G	15 35/64
SAP24HP230V1R32AO	
DIMENSIONS	
A	36 11/32
B	39 3/8
C	29 3/8
D	14 17/32
E	16 13/16
F	24 1/64
G	15 35/64




CLEARANCES

INDOOR UNIT

Minimum clearance


DIMENSIONS	
A	60
B	12
C	39
D	6
E	90

Unit: inch




OUTDOOR UNIT

Minimum clearance



NOTE:
If bottom of the unit is free of airflow obstructions similar to the mounting bracket figure, the clearance to the wall on the back can be reduced to 3 inches.



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.