

SUBMITTAL DATA

MUL30HP230V1R32AO
30000 BTU/H Multi-Zone Heat Pump System

Job Name	Location	Date
Purchaser	Engineer	
Submitted to	For	
Unit Designation	Schedule No.	



MUL30HP230V1R32AO

GENERAL FEATURES

- AHRI Certificate: [215218915 \(Non-Ducted\)](#)
- [215218920 \(Ducted\)](#)
- [215218925 \(Mixed\)](#)
- High Efficiency DC Inverter Technology
- Compact and Quiet Design
- Auto Restart on Power Outages
- Multi-point Diagnostics
- Wi-Fi Included (Factory Installed)
- Low Ambient Cooling down to -22°F (Range -22°F to 118°F)
- Low Ambient Heating down to -22°F (Range -22°F to 75°F)
- Coil (Indoor and Outdoor) Copper Tube / Aluminum Fin
- Blue Colored Fin - 500 Hrs Salt Spray Tested

MULTI-ZONE COMPATIBILITY CHART

WALL MOUNT OPTIONS

	MULTI-ZONE					
	MUL18HP230V1R32AO	MUL24HP230V1R32AO	MUL30HP230V1R32AO	MUL36HP230V1R32AO	MUL42HP230V1R32AO	MUL48HP230V1R32AO
LIVO						
System Model no.						
LIV05HP230V1R32AH	•	•	•	•	•	•
LIV07HP230V1R32AH	•	•	•	•	•	•
LIV09HP230V1R32AH	•	•	•	•	•	•
LIV12HP230V1R32AH	•	•	•	•	•	•
LIV18HP230V1R32AH		•	•	•	•	•
LIV24HP230V1R32AH			•	•	•	•
LIV30HP230V1R32AH						
LIV36HP230V1R32AH						
VIREO						
System Model no.						
VIR09HP230V1R32AH	•	•	•	•	•	•
VIR12HP230V1R32AH	•	•	•	•	•	•
VIR18HP230V1R32AH		•	•	•	•	•
VIR24HP230V1R32AH			•	•	•	•
ENVO						
System Model no.						
ENV09HP230V1R32AH	•	•	•	•	•	•
ENV12HP230V1R32AH	•	•	•	•	•	•
ENV18HP230V1R32AH		•	•	•	•	•
ENV24HP230V1R32AH			•	•	•	•
SAPPHIRE						
System Model no.						
SAP09HP230V1R32AH	•	•	•	•	•	•
SAP12HP230V1R32AH	•	•	•	•	•	•
SAP18HP230V1R32AH		•	•	•	•	•
SAP24HP230V1R32AH			•	•	•	•

ADDITIONAL INDOOR UNIT OPTIONS

	MULTI-ZONE					
	MUL18HP230V1R32AO	MUL24HP230V1R32AO	MUL30HP230V1R32AO	MUL36HP230V1R32AO	MUL42HP230V1R32AO	MUL48HP230V1R32AO
ONE WAY CASSETTE						
System Model no.						
OWC09HP230V1R32AH	•	•	•	•	•	•
OWC12HP230V1R32AH	•	•	•	•	•	•
OWC18HP230V1R32AH		•	•	•	•	•
OWC20HP230V1R32AH			•	•	•	•
CEILING CASSETTE						
System Model no.						
CAS09HP230V1R32AH	•	•	•	•	•	•
CAS12HP230V1R32AH	•	•	•	•	•	•
CAS18HP230V1R32AH		•	•	•	•	•
CAS24HP230V1R32AH			•	•	•	•
SLIM DUCT						
System Model no.						
DUC09HP230V1R32AH	•	•	•	•	•	•
DUC12HP230V1R32AH	•	•	•	•	•	•
DUC18HP230V1R32AH		•	•	•	•	•
DUC24HP230V1R32AH			•	•	•	•
FLOOR/CEILING						
System Model no.						
FLR09HP230V1R32AH	•	•	•	•	•	•
FLR12HP230V1R32AH	•	•	•	•	•	•
FLR18HP230V1R32AH		•	•	•	•	•
FLR24HP230V1R32AH			•	•	•	•
MINI-CONSOLE						
System Model no.						
CON09HP230V1R32AH	•	•	•	•	•	•
CON12HP230V1R32AH	•	•	•	•	•	•
CON18HP230V1R32AH		•	•	•	•	•

NOTE: R32 Indoor units are only compatible with R32 Outdoor units. Keep in mind, line set is always sized by the indoor unit valve diameter.

SPECIFICATIONS, FEATURES & FUNCTION SUMMARY

SYSTEM TYPE			HEAT PUMP
Outdoor Model			MUL30HP230V1R32AO
Number of Zones			2 - 4
SYSTEM PERFORMANCE (Non-Ducted Indoor Units)			
Cooling Capacity	Min - Max	Btu/h	7,198 - 32,915
	Capacity @95°F	Btu/h	28,400
Heating Capacity	Min - Max	Btu/h	11,305 - 33,000
	Capacity @47°F	Btu/h	30,000
	Capacity @17°F	Btu/h	28,000
	Capacity Max @5°F	Btu/h	27,000
SEER2			21
EER2			13.6
HSPF2			10.0
COP @5°F			2.07
SYSTEM PERFORMANCE (Ducted Indoor Units)			
Cooling Capacity	Min - Max	Btu/h	7,198 - 32,915
	Capacity @95°F	Btu/h	28,400
Heating Capacity	Min - Max	Btu/h	11,305 - 33,000
	Capacity @47°F	Btu/h	30,000
	Capacity @17°F	Btu/h	27,200
	Capacity Max @5°F	Btu/h	26,000
SEER2			18.0
EER2			12.0
HSPF2			8.1
COP @5°F			1.88
SYSTEM PERFORMANCE (Mixed Ducted and Non-Ducted Indoor Units)			
Cooling Capacity	Min - Max	Btu/h	7,198 - 32,915
	Capacity @95°F	Btu/h	28,400
Heating Capacity	Min - Max	Btu/h	11,305 - 33,000
	Capacity @47°F	Btu/h	30,000
	Capacity @17°F	Btu/h	27,600
	Capacity Max @5°F	Btu/h	26,400
SEER2			19.0
EER2			12.2
HSPF2			9.0
COP @5°F			1.81
OUTDOOR UNIT			MUL30HP230V1R32AO
Cooling Temperature Range		°F	-22 - 118
Heating Temperature Range		°F	-22 - 75
Refrigerant Type			R32
Cmpressor Type			GREE G-20 / Double Cylinder / 1 - STAGE INVERTER
Sound Pressure Level		dB(A)	62
External Dimensions (W x H x D)		in	40-10/64 x 32-33/64 x 16-52/64
Package Dimension (W x H x D)		in	43-1/32 x 34-27/32 x 19-9/16
Net Weight		lbs	145.5
Gross Weight		lbs	161.0
REFRIGERANT PIPING			
Refrigerant Charge - R32		oz	77.62
Cmpressor Type			GREE G-20 / Double Cylinder / 1 - STAGE INVERTER
Additional Charge		oz/ft	0.2
Port Size (Liquid - Gas)	Port A (in)	1/4 - 3/8	
	Port B (in)	1/4 - 3/8	
	Port C (in)	1/4 - 3/8	
	Port D (in)	1/4 - 3/8	
	Port E (in)		
Pre-Charge Length		ft	131
Pipe Length (Min - Max)		ft	10 - 263
Pipe Length to furthest Indoor Unit		ft	82
Max. Pipe Elevation		ft	82

ELECTRICAL		
Power Supply		208-230V / 1Ph / 60Hz
Voltage Range (Min - Max)	VAC	187 - 253
Rated Current - Cooling	A	20
Rated Current - Heating	A	21.7
MCA	A	23
MOCP	A	35
Suggested Breaker Size	A	25
Main Power Wire Size	AWG	Per Local Code
Interconnecting Wire Size	AWG	14 / 4
FEATURES & FUNCTIONS SUMMARY		
Inverter Type	G20	
Ultra Low Frequency Torque Control	Yes	
Compressor Type - Inverter	Yes	
Basepan With Electric Heater	High Efficiency Rotary	
Indoor & Outdoor Fin Coating (Blue Fin)	Yes	
Intelligent Defrosting	Yes	
Intelligent Preheating	Yes	
Low Voltage Startup	Yes	
Memory/Power Failure Recovery	Yes	
Self Diagnosis	Yes	

ALLOWABLE COMBINATIONS CAPACITIES

MODEL NUMBER	POSSIBLE COMBINATIONS*	COOLING CAPACITY (Btu/h)					HEATING CAPACITY (Btu/h)				
		ZONE1	ZONE2	ZONE3	ZONE4	ZONE5	ZONE1	ZONE2	ZONE3	ZONE4	ZONE5
MUL30HP230V1R32AO	5K+5K+5K	5,000	5,000	5,000			6,000	6,000	6,000		
MUL30HP230V1R32AO	7K+7K+7K	7,000	7,000	7,000			8,000	8,000	8,000		
MUL30HP230V1R32AO	5K+5K+7K	5,000	5,000	6,000			6,000	6,000	8,000		
MUL30HP230V1R32AO	5K+7K+7K	5,000	7,000	7,000			6,000	8,000	8,000		
MUL30HP230V1R32AO	5K+5K+5K+5K	5,000	5,000	5,000	5,000		6,000	6,000	6,000	6,000	
MUL30HP230V1R32AO	7K+7K+7K+7K	7,000	7,000	7,000	7,000		8,000	8,000	8,000	8,000	
MUL30HP230V1R32AO	5K+5K+5K+7K	5,000	5,000	5,000	7,000		6,000	6,000	6,000	8,000	
MUL30HP230V1R32AO	5K+5K+7K+7K	5,000	5,000	7,000	7,000		6,000	6,000	8,000	8,000	
MUL30HP230V1R32AO	5K+7K+7K+7K	5,000	7,000	7,000	7,000		6,000	8,000	8,000	8,000	
MUL30HP230V1R32AO	9K+9K	9,000	9,000				9,000	9,000			
MUL30HP230V1R32AO	9K+12K	9,000	12,000				9,000	12,000			
MUL30HP230V1R32AO	9K+18K	9,000	18,000				9,000	18,000			
MUL30HP230V1R32AO	9K+24K	7,745	20,655				8,182	21,818			
MUL30HP230V1R32AO	12K+12K	12,000	12,000				12,000	12,000			
MUL30HP230V1R32AO	12K+18K	11,360	17,040				12,000	18,000			
MUL30HP230V1R32AO	12K+24K	9,467	18,933				10,000	20,000			
MUL30HP230V1R32AO	18K+18K	14,200	14,200				15,000	15,000			
MUL30HP230V1R32AO	18K+24K	12,171	16,229				12,857	17,143			
MUL30HP230V1R32AO	9K+9K+9K	9,000	9,000	9,000			9,000	9,000	9,000		
MUL30HP230V1R32AO	9K+9K+12K	8,520	8,520	11,360			9,000	9,000	12,000		
MUL30HP230V1R32AO	9K+9K+18K	7,100	7,100	14,200			7,500	7,500	15,000		
MUL30HP230V1R32AO	9K+9K+24K	6,086	6,086	16,229			6,429	6,429	17,143		
MUL30HP230V1R32AO	9K+12K+12K	7,745	10,327	10,327			8,182	10,909	10,909		
MUL30HP230V1R32AO	9K+12K+18K	6,554	8,738	13,108			6,923	9,231	13,846		
MUL30HP230V1R32AO	9K+12K+24K	5,680	7,573	15,147			6,000	8,000	16,000		
MUL30HP230V1R32AO	9K+18K+18K	5,680	11,360	11,360			6,000	12,000	12,000		
MUL30HP230V1R32AO	12K+12K+12K	9,467	9,467	9,467			10,000	10,000	10,000		
MUL30HP230V1R32AO	12K+12K+18K	8,114	8,114	12,171			8,571	8,571	12,857		
MUL30HP230V1R32AO	9K+9K+9K+9K	7,100	7,100	7,100	7,100		7,500	7,500	7,500	7,500	
MUL30HP230V1R32AO	9K+9K+9K+12K	6,554	6,554	6,554	8,738		6,923	6,923	6,923	9,231	
MUL30HP230V1R32AO	9K+9K+9K+18K	5,680	5,680	5,680	11,360		6,000	6,000	6,000	12,000	
MUL30HP230V1R32AO	9K+9K+12K+12K	6,086	6,086	8,114	8,114		6,429	6,429	8,571	8,571	
MUL30HP230V1R32AO	9K+12K+12K+12K	5,680	7,573	7,573	7,573		6,000	8,000	8,000	8,000	

Outdoor Unit & Possible Indoor Unit Combinations with AHRI Certified Performance


*You may substitute the 9K unit with a 5K or 7K High Wall unit, find complete capacity information in the extended ratings chart.

DIMENSIONS

OUTDOOR UNIT

Unit: inch


MUL30HP230V1R32AO
DIMENSIONS



CLEARANCES

OUTDOOR UNIT

Minimum clearance



Specifications are subject to change without notice. Manufacturer reserves the right to discontinue or modify specifications or designs without notice or without incurring obligations. All Rights reserved.