

# PBX SERIES

## Industrial Portable Blowers

NEW LOOK - The PBX Series were recently redesigned and reconstructed to ensure the best performance possible. These portable blowers are available in sizes ranging from 30"- 48", with a max CFM of 23,500. These units are rugged and durable, constructed with OSHA-compliant corrosion and dent-proof high density polyethylene housing. Fans are lightweight and easily moved where needed. The possibilities are endless; use this fan anywhere quick cooling and powerful airflow is needed.

### SIZE

30", 36", 42" & 48"

### HOUSING

CORROSION &  
DENT PROOF  
HIGH-DENSITY  
POLYETHYLENE

### MOTOR

DIRECT &  
BELT DRIVE

PBX - D STANDARD MODEL



PBX - B STANDARD MODEL



BELT DRIVE	MFG CATALOG NUMBER	MFG MODEL NUMBER	FAN		WHEEL SIZE	MOTOR HP	VELOCITY PROFILE	AMPS	WT. (LBS.)
			SIZE	TYPE			CFM / Area Sq Ft		
	08211402	PBX 36-B	36"	STANDARD	8"	1/2	14000 / 360	8.0	120
08211502	PBX 42-B	42"	STANDARD	10"	3/4	17500 / 420	11.0	135	
08211602	PBX 48-B	48"	STANDARD	10"	1	23500 / 550	15.0	155	

DIRECT DRIVE	MFG CATALOG NUMBER	MFG MODEL NUMBER	FAN		WHEEL SIZE	MOTOR HP	VELOCITY PROFILE	AMPS	WT. (LBS.)
			SIZE	TYPE			CFM / Area Sq Ft		
	08211002	PBX 30-D	30"	STANDARD	8"	1/4	7200 / 250	2.5	65
08211102	PBX 36-D	36"	STANDARD	10"	1/3	11500 / 320	5.5	82	
08211202	PBX 42-D	42"	STANDARD	10"	1/2	15000 / 340	6.0	102	

