

PVM18C

PVM18C

Product Description

The VersaMist® reduces air temperature by as much as 30°F. Low pressure mist technology combines fine mist and high speed air movement for highly effective “person” cooling indoors and outdoors. The 18”, UL507 rated, 3-speed fan provides up to seven hours of use and is ergonomically designed for portability. The VersaMist is ideal for cooling work areas, rehabilitation stations, outdoor events, emergency workers, patios, and sidelines.

Features

Produces up to 2600 cfm of cooling breeze

Available with or without wheels

Wheeled version has integrated handle and wheels for easy movement

10 or 14 gallon built in water reservoir for portability

Adjustable fan head for targeted cooling

Rapid mist evaporation produces 16,000 BTU/hour (1.4 tons) of cooling

Pump and fan assembly separates from the reservoir for quick and effortless set up, cleaning and storage

Integral tip switch to turn power off if unit is knocked over

25 foot outdoor rated power cord with integrated GFCI plug for use in standard wall outlet

UL507 rated for outdoor use



Specifications

Blade Color	White
Brand	Schaefer
Cfm (free Air)	2200
Cooling Capacity (1000 Btu)	16
Drive	Direct
Operating Temperature (high) F	40C
Phase	1
Speeds	3
Watts	250
Cfm/watt (free	13

Cfm (medium)	1800
Operating Temperature (low) F	0C
Power (hp)	1/4
Product Net Weight (lbs)	43
Performance Test #	644
Switch	On product
Voltage	115
Blade Material	Aluminum
Cfm (high)	2200

Cord Length (feet)	25
Distinguishing Feature	Cools Air via Evaporative Cooling
Fixed Or Portable	Portable
Guard Material	Powder Coated Steel
Maximum Water Pressure (psi)	TBD
Oscillating	No
Product Certifications	cULus

Air)	
Cord	Included - Wired
Diameter (inches)	18
Frequency (hz)	60
Guard Color	White
Nameplate Amps	2.2
Number Of Wings	3

Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White
Product Shipping Dimensions (in)	(FAN) 22 X 22 X 26 / (TANK) 24 X 19 X 15
Speed Control Compatible?	No
Able To Ship Small Parcel	Yes
Cfm (low)	1400
Cfm Range (free Air)	1001 - 2500

On Board Reservoir	Yes
Water Usage At Standard Pressure	TBD
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	TBD
Cfm (@0.05")	TBD