



# PINNACLE

## SINGLE-ZONE SERIES

14 YEAR  
WARRANTY

WIFI &  
SMART HOME

### THE HALLMARK OF ELEGANCE & FUNCTIONALITY.

With the Stealth wall mount ductless mini-splits, you can keep any room comfortable without sacrificing aesthetics. The quiet, unobtrusive design delivers advanced performance with industry-best energy efficiency rating of as high as 38 SEER in cooling and 15 HSPF in heating.

- HIGH EFFICIENCY, UP TO 38 SEER / 15 HSPF
- IDEAL FOR HARSH CLIMATES: -31° F - 118° F
- SLEEP FUNCTION
- SELF DIAGNOSIS
- INTELLIGENT DEFROST
- FAN SPEED CONTROL
- LOW VOLTAGE START-UP



| MODEL                                    |       | SC-09WPL-HP230   | SC-12WPL-HP230                | SC-18WPL-HP230             | SC-24WPL-HP230             |
|--|-------|--|-------------------------------|----------------------------|----------------------------|
| System Type                              |       | HEAT PUMP  |                               |                            |                            |
| <b>SYSTEM PERFORMANCE</b>                |       |  |                               |                            |                            |
| Cooling Capacity (Min-Max)               | Btu/h | 9000 (1535 - 12966)  | 12000 (2900 - 15354)          | 18000 (4094 - 21837)       | 22000 (6800 - 30700)       |
| Heating Capacity (Min-Max)               | Btu/h | 9000 (2388 - 13648)  | 12200 (3071 - 18766)          | 18000 (4094 - 24566)       | 24000 (6800 - 32000)       |
| SEER / EER                               |       | 38 / 16.67   | 30.5 / 15.3                   | 24.5 / 13.54               | 21.5 / 13                  |
| HSPF / COP                               |       | 15 / 4.47  | 14 / 3.8                      | 12 / 3.52                  | 12 / 3.5                   |
| Energy Star®                             |       | YES  |                               |                            |                            |
| Cooling Temperature Range                | °F    | 0 - 129  | 0 - 129                       | 0 - 129                    | 0 - 129                    |
| Heating Temperature Range                | °F    | -22 - 75   | -22 - 75                      | -22 - 75                   | -22 - 75                   |
| <b>INDOOR UNIT</b>                       |       |  |                               |                            |                            |
|  |       | SC-09WPL-HP230   | SC-12WPL-HP230                | SC-18WPL-HP230             | SC-24WPL-HP230             |
| Air flow (Min-Max)                       | CFM   | 206 - 424  | 235 - 500                     | 353 - 736                  | 383 - 824                  |
| Sound Pressure Level (Cooling / Heating) | dB(A) | 19 - 46 / 19 - 46  | 22 - 49 / 22 - 49             | 34 - 51 / 34 - 51          | 27 - 54 / 37 - 55          |
| Dehumidification                         | pt/hr | 1.69   | 2.96                          | 3.8                        | 4.23                       |
| Condensate Drain Size (OD)               | in    | 5/8  | 5/8                           | 5/8                        | 5/8                        |
| Unit Dimension (WxHxD)                   | in    | 39 7/8 x 12 1/8 x 8 3/4  | 39 7/8 x 12 1/8 x 8 3/4       | 44 3/16 x 13 x 9 13/16     | 44 3/16 x 13 x 9 13/16     |
| Package Dimension (WxHxD)                | in    | 42 7/16 x 14 13/16 x 11 13/16  | 42 7/16 x 14 13/16 x 11 13/16 | 46 7/8 x 16 x 13 3/16      | 46 7/8 x 16 x 13 3/16      |
| Weight (Net / Gross)                     | lbs   | 29.8 / 36.4  | 29.8 / 36.4                   | 36.4 / 44.1                | 35.3 / 41.9                |
| <b>OUTDOOR UNIT</b>                      |       |  |                               |                            |                            |
|  |       | SC-09ZPL-HP230   | SC-12ZPL-HP230                | SC-18ZPL-HP230             | SC-24ZPL-HP230             |
| Compressor Type                          |       | GREE G-10 / 2 - STAGE INVERTER   |                               |                            |                            |
| Sound Pressure Level (Cooling / Heating) | dB(A) | 57 / 57  | 53 / 53                       | 59 / 59                    | 59 / 59                    |
| Unit Dimension (WxHxD)                   | in    | 35 13/32 x 23 1/2 x 14 7/8   | 35 13/32 x 23 1/2 x 14 7/8    | 38 5/8 x 31 1/8 x 16 13/16 | 38 5/8 x 31 1/8 x 16 13/16 |
| Package Dimension (WxHxD)                | in    | 37 3/16 x 24 13/16 x 16 7/16   | 37 3/16 x 24 13/16 x 16 7/16  | 42 1/2 x 33 1/8 x 19 1/8   | 42 1/2 x 33 1/8 x 19 1/8   |
| Weight (Net / Gross)                     | lbs   | 99.2 / 105.8   | 105.8 / 49.4                  | 141.1 / 152.1              | 147.7 / 158.8              |
| Refrigerant Charge - R410A               | oz    | 50.4   | 49.4                          | 70.6                       | 81.1                       |
| Coil Type                                |       | Aluminum Fin-Copper Tube / Acrylic Resin Protection                    |                               |                            |                            |
| <b>REFRIGERANT PIPING</b>                |       |  |                               |                            |                            |
| Line Set Size (Liquid - Gas)             | in    | 1/4 - 1/2  | 1/4 - 1/2                     | 1/4 - 5/8                  | 1/4 - 5/8                  |
| Pre-Charge Length                        | ft    | 25   |                               |                            |                            |
| Pipe Length (Min / Max)                  | ft    | 10 / 49  | 10 / 98                       | 10 / 131                   | 10 / 164                   |
| Max. Pipe Elevation                      | ft    | 33   | 49                            | 66                         | 98                         |
| <b>ELECTRICAL</b>                        |       |  |                               |                            |                            |
| Power Supply                             |       | 208-230V / 1Ph / 60Hz  |                               |                            |                            |
| Rated Current Cooling                    | amps  | 6.2  | 6.5                           | 10.8                       | 16.4                       |
| Rated Current Heating                    | amps  | 6.9  | 6.9                           | 10.8                       | 16.4                       |
| MCA                                      | amps  | 9  | 9                             | 22                         | 22                         |
| MOCP                                     | amps  | 15   | 15                            | 30                         | 35                         |
| Main Power Wire Size                     | AWG   | Per Local Code   |                               |                            |                            |
| Interconnecting Wire Size                | AWG   | 14 / 4   |                               |                            |                            |
| LIMITED WARRANTY                         |       | 5 year parts, 14 year compressor replacement with online registration. |                               |                            |                            |