

SFT-1200

SFT-1200

Product Description

Schaefer shutter-style exhaust fans offer an energy efficient solution to meet low to medium exhaust airflow requirements. These exhaust fans work perfectly in thin-walled buildings requiring exhaust fans with a low profile such as greenhouses.

Features

Low profile for thin-walled buildings and where space is limited

Aluminum blade and rugged PVC shutter for durability and longer life

Heavy-duty totally enclosed and maintenance free motors

Mounts flush to the exterior wall

Available in 12", 16", 20" and 24" sizes



Specifications

Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	TBD
Cfm (with 25' Of Duct)	TBD
Drive	Direct
Housing Material	TBD
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	12 5/8" x 12 5/8"
Speeds	1
Cfm/watt (free Air)	TBD
Cord	Not included
Diameter (inches)	12

Frequency (hz)	60
Guard Color	White
Nameplate Amps	0.9
Number Of Wings	5
Operating Temperature (low) F	TBD
Power (hp)	1/30
Product Net Weight (lbs)	10
Voltage	115
Blade Material	Aluminum
Cfm (high)	TBD
Product Color	White
Product Shipping Dimensions (in)	18 x 18 x 10
Speed Control Compatible?	Yes

Able To Ship Small Parcel	Yes
Cfm Range (free Air)	<1000
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	TBD
Cfm (@0.05")	760