



SFT-2000A

SFT-2000A

Product Description

Schaefer shutter-style exhaust fans offer an energy efficient solution to meet low to medium exhaust airflow requirements. These exhaust fans work perfectly in thin-walled buildings requiring exhaust fans with a low profile such as greenhouses.

Features

Low profile for thin-walled buildings and where space is limited

Aluminum blade and rugged PVC shutter for durability and longer life

Heavy-duty totally enclosed and maintenance free motors

Mounts flush to the exterior wall

Available in 12", 16", 20" and 24" sizes

Specifications



Air Velocity (@ 10')	TBD
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	TBD
Cfm (with 25' Of Duct)	TBD
Drive	Direct
Housing Material	TBD
Operating Temperature (high) F	TBD
Phase	1
Rough-in Dimensions	20 5/8" x 20 5/8"
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	TBD
Cord	Not included

Diameter (inches)	20
Frequency (hz)	60
Guard Color	White
Nameplate Amps	3.8/1.9
Number Of Wings	4
Operating Temperature (low) F	TBD
Power (hp)	1/3
Product Dimensions (L X W X H Inches)	TBD
Product Net Weight (lbs)	TBD
Voltage	115/230
Air Velocity (@ 5 Times Diameter)	TBD
Blade Material	Aluminum
Cfm (high)	TBD
Product Color	White

Speed Control Compatible?	No
Cfm Range (free Air)	TBD
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Oscillating	No
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White
Cfm/watt (@0.10")	TBD
Cfm (@ 0.10")	TBD
Cfm/watt (@0.05")	TBD
Cfm (@0.05")	TBD