TPI Industrial Mini-Blowers





WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.



MBM-W (Optional Wall/ Ceiling Mount)

TOTALLY ENCLOSED MOTOR ALLOWS MINI-BLOWER TO BE USED IN DIRTY OR DUSTY ENVIRONMENTS.

AVAILABLE AS FLOOR MODEL OR YOKE MOUNTED MODEL THAT CAN BE DIRECTLY BOLTED TO ANY SURFACE OR USED WITH OPTIONAL WALL/CEILING MOUNT.

Features

- · Floor models have rotary switch
- · Yoke mounted models have pull chain switch
- · SJT type 3 conductor, 10' long cord
- Aluminum blade
- · Spiral, wire front and rear guards
- · Corrosion and dent proof high density polyethylene housing
- Meets OSHA standards
- 1 year limited warranty
- · Made in U.S.A. with domestic and foreign components

Motor Specifications

- 1-Phase
- 1/4 HP
- · Ball bearing
- · 2-Speed
- · Totally enclosed
- · Permanently lubricated · Permanent split capacitor

Standard Models

| MFG CATALOG | MFG MODEL | FAN | | CFM* / RPM | | VELOCITY PROFILE | DIMENSIONS | | AMPS | WT. | LIST | |
|---|-----------|-------------|------|------------|--------|------------------|------------|-------|---------|--------|-------|------|
| NUMBER | NUMBER | TYPE | SIZE | HIGH | LOW | CFM / Area Sq Ft | "H" | "W" | "D" | (High) | (LBS) | LIST |
| 08743502 | MB 24-DF | FLOOR STYLE | 24" | 3300 / | 2900 / | 5200 / 240 | 29 ½" | 28 ½" | 14 1/4" | 2.2 | 52 | 767 |
| 08743602 | MB 24-DY | YOKE STYLE | 24 | 1140 | 1070 | | 29" | 28 ½" | 14 1/4" | | 52 | 767 |
| 08743702 | MB 30-DF | FLOOR STYLE | 30" | 4400 / | 3900 / | 7000 / 250 | 38 ½" | 37 ½" | 14 ½" | 2.5 | 58 | 847 |
| 08743802 | MB 30-DY | YOKE STYLE | 30 | 1040 | 730 | | 38" | 37 ½" | 14 ½" | 2.5 | 58 | 847 |
| 07989002 MBM-W OPTIONAL WALL/CEILING MOUNT FOR YOKE STYLE MINI-BLOWER | | | | | | | | | 4 | 155 | | |

^{*}Measured 2 feet from face of fan

TPI Industrial High Velocity Blowers

NEW PRODUCT for 2020





WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Features

- · Aluminum blade
- · Spiral, wire front and rear guards
- · Wall and ceiling mounting options
- · Gray epoxy powdercoated housing
- · 2 year limited warranty
- · Made in U.S.A.
- Stationary
- · Direct drive

Motor Specifications

- 1-Phase
- · Single speed
- · Ball bearing motor
- 373 & 746 watts
- 1/2 or 1 HP
- · Automatic thermal protection

TEAO

| MOUNTING BRACKETS | | | | | | | | | |
|-----------------------|---------------------|------|--------------|------|--|--|--|--|--|
| MFG CATALOG NUMBER | MFG MODEL NUMBER | SIZE | WT. (LBS) | LIST | | | | | |
| 08197502 | HV-1 | 18" | 14 | 115 | | | | | |
| 08197602 | HV-2 | 24" | 22 | 153 | | | | | |
| 08197702 | HV-3 | 30" | 24 | 181 | | | | | |

Standard Models

| SIZE | MFG CATALOG | MFG MODEL | VOLTS | DUACE | HP | MATTO | CFM / RPM | DIMENSIONS | | | AMPS | WT. | PRICE |
|--------|---------------|-----------|---------|-------|---------|-----------|-------------|------------|--------|--------|-------|-------|-------|
| NUMBER | NUMBER | VOLIS | PHASE | пР | WATTS | CFM / RPM | "H" | "W" | "D" | (High) | (LBS) | PRICE | |
| | HV18-120V | 08195602 | 120 | 1 | 1/2 | 373 | 3000 / 1725 | 25.12" | 23.63" | 13.5" | 5.0 | 45 | 1088 |
| | HV18-208/240V | 08195702 | 208/240 | | | | | | | | 2.6 | | |
| 18" | HV18-277V | 08195802 | 277 |] ' | | | | | | | 2.1 | | |
| | HV18-480V | 08195902 | 480 | 3 | | | | | | | 1.3 | | |
| | HV18-480V-3 | 08197202 | 480 | | | | | | | | 1.0* | | 1376 |
| | HV24-120V | 08196002 | 120 | 1 3 | | | 5290 / 1725 | 30.5" | 29.63" | 13.5" | 5.0 | 58 | 1375 |
| | HV24-208/240V | 08196102 | 208/240 | | | | | | | | 2.6 | | |
| 24" | HV24-277V | 08196202 | 277 | | | | | | | | 2.1 | | 13/3 |
| | HV24-480V | 08196302 | 480 | | | | | | | | 1.3 | | |
| | HV24-480V-3 | 08197302 | 480 | | | | | | | | 1.0* | | 1663 |
| 30" | HV30-120V | 08196402 | 120 | 1 | 1 | 746 | 9000 / 1700 | 38" | 34.63" | 16" | 10.0 | 85 | 1988 |
| | HV30-208/240V | 08196502 | 208/240 | | | | | | | | 4.7 | | |
| | HV30-277V | 08196602 | 277 | | | | | | | | 3.6 | | |
| | HV30-480V | 08196702 | 480 | | | | | | | | 2.1 | | |
| | HV30-480V-3 | 08197402 | 480 | 3 | | | | | | | 1.7* | | 2438 |