

3320 Series Commercial Fan Forced Wall Heater



Manufactured in U.S.A.

Features

- Disconnect switch.
- Automatic fan delay circuit.
- Powder coated 18 Gauge steel grill with extruded Aluminum front frame.
- Automatic reset thermal limit.
- Steel block fin element.
- Vane axial fan blade:
 - 600 RPM motor; 175 CFM
- Rough-in dimensions:
 - 14-3/16" Wide x 19-15/16" High x 4" Deep
- Grill dimensions:
 - 15-29/32" Wide x 20-27/32" High
- Built-In tamperproof thermostat.



Product Specifications

Furnish and install Heavy-Duty Forced Air wall heaters, where specified. The heaters shall be constructed of a heavy 18 Gauge steel housing with an extruded Aluminum frame. The rough-in dimensions are 19-5/16" High x 14-3/16" Wide x 4" Deep. The units shall be available in ratings from 750 to 4800 Watts at 240, 208, and 277 Volts. The heaters shall have a low-speed 600 RPM, 4-pole motor which drives a vane axial blower to deliver a quiet 175 CFM of down flow air. The heating element shall be of the sealed tubular type with large, parallel steel fins for quick heat transfer. Unit shall have as a standard, a thermal overload cut-off for added safety, fan delay switch and built-in tamperproof thermostat which shall be calibrated to provide a range of 55°F. to 85°F. and manual disconnect switch.

Optional accessories shall include a surface and semi-recess mounting adapter. All heaters shall be listed by ETL. The heating element shall be supplied with a manufactures 1-year limited warranty.

Standard Models

UPC#	MODEL	WATTS	BTU's	VOLTS	AMPS	WT. LBS.	LIST
686334	IN-BUILT SINGLE POLE TAMPERPROOF THERMOSTAT (50° - 90° TEMPERATURE RANGE) FOR DOUBLE POLE THERMOSTAT REPLACE "TT" IN MODEL NUMBER WITH "T2"						
382052	E3321TD-RP	750	2560	120	6.25	26	589
381994	E3322TD-RP	1000	3413		8.3		
380881	E3323TD-RP	1500	5120		12.5		
380935	F3326TD-RP	4000	13800	208	19.2	27	600
381024	F3327TD-RP	4800	16560		23		630
380942	HF3323TD-RP	1500 / 1125	5120 / 3840	240 / 208	6.2 / 5.4	29	600
380959	HF3324TD-RP	2000 / 1500	6284 / 5120		8.3 / 7.2		
380966	HF3325TD-RP	3000 / 2250	10350 / 7763		12.5 / 10.8		
380973	HF3326TD-RP	4000 / 3000	13800 / 10350	240	16.7/14.4	27	624
381031	H3327TD-RP	4800	16560		20		
380980	G3323TD-RP	1500	5120	277	4.1	29	599
380997	G3324TD-RP	2000	6284		7.2		
381000	G3325TD-RP	3000	10350		10.8		
381017	G3326TD-RP	4000	13800		14.4		
381048	G3327TD-RP	4800	16560		17.3		617

Accessories

UPC 686334	MODEL	DESCRIPTION	TYPE	WT. lbs.	LIST
377850	BOX 3310	Additional Rough-in Box		3	91
378451	3320EX33	4" Surface Mounting Frame	Field Installed	1	81
382939	3320EX16	2" semi recess extender		1	69
----	Suffix - HD	16 Gauge Steel Heavy Duty Grill	Factory Installed	2	91

4400 Series Low Profile Commercial Fan Forced Wall Heater - With Wall Box

- Powder coated 20 Gauge steel front with extruded Aluminum frame.
- Manual reset thermal limit.
- Finned tubular steel element.
- Propeller style fan blade - 2200 RPM/70 CFM
- Weight 9 lbs.
- Rough in dimensions:
 - 14 1/2" Wide x 7 1/8" High x 3 1/2" Deep
- Grill dimensions: 16 7/8" Wide x 8" High
- Unit not approved for ceiling mount applications.
- Unit can be positioned to allow left, right or top discharge.



Manufactured in U.S.A.



Standard Models

UPC 686334	MODEL	VOLTS	WATTS	MAX BTU'S	AMPS	LIST
DOUBLE POLE IN-BUILT THERMOSTAT (RANGE 50° - 90° F)						
328326	F4420T2RP	208	2000	6826	9.6	291
328333	HF4475T2RP	240/208	750 / 562	2560 / 1920	3.1 / 2.7	
328340	HF4410T2RP		1000 / 750	3413 / 2560	4.2 / 3.6	
328357	HF4415T2RP		1500 / 1125	5120 / 3840	6.3 / 5.4	
328364	HF4420T2RP		2000 / 1500	6826 / 5120	8.3 / 7.2	
SINGLE POLE IN-BUILT THERMOSTAT (RANGE 50° - 90° F)						
328371	E4475TRP	120	750	2560	6.25	274
328388	E4410TRP		1000	3413	8.33	
328395	E4415TRP		1500	5120	12.5	
328401	F4420TRP		2000	6826	9.6	

Accessories

UPC 686334	MODEL	DESCRIPTION	WT. LBS.	LIST
329910	4400EX8	1" SEMI RECESSING EXTENDER	2	40
329903	4400EX16	2" SEMI RECESSING EXTENDER	3	43
329897	4400EX32	4" SURFACE MOUNTING FRAME	4	45
328449	4300PB	WALL PLATE ADAPTOR (OD 21.5"x12.25")	1	29