

TW20B

TW20B

Product Description

Geared for performance, Twister's oscillating motor utilizes highest quality metal gear design for unparalleled strength, greater load capacity and higher accuracy. Whether aimed at a workstation using a standard wall mount or down an aisle or assembly line using a pedestal, Twister provides the versatility and performance needed to improve worker productivity and safety.

Features

Schaefer oscillation technology

2-speed high efficiency motor with 10 foot cord

OSHA compliant guards, available in black or white

90 degrees of total oscillation

45 degrees of fan head adjustability up or down

Four sizes 20", 24", 30" and 36" for optimizing air flow needs

Low noise levels, quieter than conversational voice

Fixed or portable mounting capabilities

Two year warranty

Assembled in the USA



Specifications

Blade Color	Metallic
Brand	Schaefer
Drive	Direct
Phase	1
Speeds	2
Vfd Compatible	No
Cfm/watt (free Air)	14.0
Cord	Included - Wired
Diameter (inches)	20
Frequency (hz)	60
Guard Color	Black

Power (hp)	1/4
Product Net Weight (lbs)	31
Performance Test #	101
Switch	On product
Voltage	115
Maximum Rpm	1075
Blade Material	Aluminum
Cfm (high)	4100
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	Black
Product Shipping	23 x 23 x 19

Cfm (low)	3400
Cfm Range (free Air)	2501 - 5000
Cord Length (feet)	10
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Mount Type Recommended	WMTA24-B
Oscillating	Yes
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA

Nameplate Amps	3
Number Of Wings	3

Dimensions (in)	
Speed Control Compatible?	No
Able To Ship Small Parcel	Yes

Cfm/watt (@0.10")	TBD
Cfm/watt (@0.05")	TBD