



TW24HVW

TW24HVW

Product Description

Geared for performance, Twister's oscillating motor utilizes highest quality metal gear design for unparalleled strength, greater load capacity and higher accuracy. Whether aimed at a workstation using a standard wall mount or down an aisle or assembly line using a pedestal, Twister provides the versatility and performance needed to improve worker productivity and safety.

Features

Schaefer oscillation technology

2-speed high efficiency motor with 10 foot cord

OSHA compliant guards, available in black or white

90 degrees of total oscillation

45 degrees of fan head adjustability up or down

Four sizes 20", 24", 30" and 36" for optimizing air flow needs

Low noise levels, quieter than conversational voice

Fixed or portable mounting capabilities

Two year warranty

Assembled in the USA



Specifications

Air Velocity (@ 10')	950
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	6700
Drive	Direct
Phase	1
Speeds	2
Vfd Compatible	No
Cfm/watt (free Air)	15.8
Cord	Included - Wired
Diameter (inches)	24

Guard Color	White
Nameplate Amps	5.9
Number Of Wings	3
Power (hp)	1/2
Product Dimensions (L X W X H Inches)	26.5" x 17.5"
Product Net Weight (lbs)	45
Switch	On product
Voltage	115
Maximum Rpm	1075
Blade Material	Aluminum

Product Shipping Dimensions (in)	27 x 27 x 19
Speed Control Compatible?	No
Able To Ship Small Parcel	Yes
Cfm (low)	6200
Cfm Range (free Air)	5001 - 10000
Cord Length (feet)	10
Oscillating	Yes
Sound Level (dda @ 10')	68
Country Of	US

Frequency (hz)	60
----------------	----

Cfm (high)	6700
Cfm Calculation Standard	ANSI/AMCA Standard 230-99

Origin	
Housing Color	White