

TW30B

TW30B

Product Description

Geared for performance, Twister's oscillating motor utilizes highest quality metal gear design for unparalleled strength, greater load capacity and higher accuracy. Whether aimed at a workstation using a standard wall mount or down an aisle or assembly line using a pedestal, Twister provides the versatility and performance needed to improve worker productivity and safety.

Features

Schaefer oscillation technology

2-speed high efficiency motor with 10 foot cord

OSHA compliant guards, available in black or white

90 degrees of total oscillation

45 degrees of fan head adjustability up or down

Four sizes 20", 24" and 30" for optimizing air flow needs

Low noise levels, quieter than conversational voice

Fixed or portable mounting capabilities

Two year warranty

Assembled in the USA



Specifications

Air Velocity (@ 10')	1100
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	9600
Drive	Direct
Phase	1
Speeds	2
Vfd Compatible	No
Cfm/watt (free Air)	20.3
Cord	Included - Wired
Diameter (inches)	30

Number Of Wings	3
Power (hp)	1/2
Product Dimensions (L X W X H Inches)	TBD
Product Net Weight (lbs)	55
Performance Test #	702
Switch	On product
Voltage	115
Air Velocity (@ 5 Times Diameter)	TBD
Blade Material	Aluminum
Cfm (high)	9600

Able To Ship Small Parcel	No
Cfm (low)	8500
Cfm Range (free Air)	10001 - 15000
Cord Length (feet)	10
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel
Mount Type Recommended	WMTA30-B
Oscillating	Yes
Sound Level (dda @ 10')	71

Frequency (hz)	60
Guard Color	Black
Nameplate Amps	5.9

Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	Black
Product Shipping Dimensions (in)	34 x 34 x 20
Speed Control Compatible?	No

Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Cfm/watt (@0.10")	TBD
Cfm/watt (@0.05")	TBD