



TW30B-PRB

TW30B-PRB

Product Description

Geared for performance, Twister's oscillating motor utilizes highest quality metal gear design for unparalleled strength, greater load capacity and higher accuracy. Whether aimed at a workstation or down an assembly line, Twister provides the versatility and performance needed to improve worker productivity and safety.

Features

Schaefer oscillation technology

2-speed high efficiency motor with 10 foot cord

OSHA compliant guards, available in black or white

90 degrees of total oscillation

45 degrees of fan head adjustability up or down

Four sizes 20", 24", 30" and 36" for optimizing air flow needs

Low noise levels, quieter than conversational voice

Fixed or portable mounting capabilities

Two year warranty

Assembled in the USA



Specifications

Air Velocity (@ 10')	1100
Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	9600
Drive	Direct
Phase	1
Speeds	2
Vfd Compatible	No
Cfm/watt (free Air)	19.7
Cord	Included - Wired
Diameter (inches)	30

Nameplate Amps	5.9
Number Of Wings	3
Power (hp)	1/2
Product Dimensions (L X W X H Inches)	TBD
Product Net Weight (lbs)	TBD
Performance Test #	701
Switch	On product
Voltage	115
Maximum Rpm	1075
Air Velocity (@ 5 Times Diameter)	TBD

Speed Control Compatible?	No
Cfm (low)	8500
Cfm Range (free Air)	5001 - 10000
Cord Length (feet)	10
Fixed Or Portable	Portable
Guard Material	Powder Coated Steel
Oscillating	Yes
Sound Level (dda @ 10')	71
Country Of Origin	US

Frequency (hz)	60
Guard Color	Black
Mount Type Included	Pedestal

Blade Material	Aluminum
Cfm (high)	9600
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	Black

Guard Spacing (inches)	1/2 OSHA
Cfm/watt (@0.10")	TBD
Cfm/watt (@0.05")	TBD