

## VK12TF-SPM-W

### VK12TF-SPM-W

#### Product Description

Schaefer pole mounted tent fans are ideal for tent cooling, heat circulation and detaching bugs. The all-white 12" fans blend in with most tents and are so quiet you don't hear them, you only feel them. Simply mount them on the tent side poles and turn them on. Use one tent fan every 15-20 feet.

#### Features

Mounts onto tent poles, saving floor space

Wide variety of mounting options available for flexible and easy installation

Quiet operation, high efficiency and output

Easily stored and transported

Misting kits available for even greater cooling

Various mounting options available.

Two year warranty

Made in the USA



#### Specifications

|                             |                  |
|-----------------------------|------------------|
| <b>Air Velocity (@ 10')</b> | TBD              |
| <b>Blade Color</b>          | Metallic         |
| <b>Brand</b>                | Schaefer         |
| <b>Cfm (free Air)</b>       | 1510             |
| <b>Drive</b>                | Direct           |
| <b>Mount Included</b>       | VS12SPM          |
| <b>Phase</b>                | 1                |
| <b>Speeds</b>               | 1                |
| <b>Vfd Compatible</b>       | No               |
| <b>Cfm/watt (free Air)</b>  | 14.4             |
| <b>Cord</b>                 | Included - Wired |
| <b>Diameter (inches)</b>    | 12               |
| <b>Frequency (hz)</b>       | 60/50            |

|                                          |          |
|------------------------------------------|----------|
| <b>Guard Color</b>                       | White    |
| <b>Mount Type Included</b>               | Pole     |
| <b>Nameplate Amps</b>                    | 1.3/.65  |
| <b>Number Of Wings</b>                   | 3        |
| <b>Bess Lab Performance Test #</b>       | 12369    |
| <b>Power (hp)</b>                        | 1/10     |
| <b>Product Net Weight (lbs)</b>          | 20       |
| <b>Switch</b>                            | On cord  |
| <b>Voltage</b>                           | 115/230  |
| <b>Maximum Rpm</b>                       | 1725     |
| <b>Air Velocity (@ 5 Times Diameter)</b> | TBD      |
| <b>Blade Material</b>                    | Aluminum |

|                                         |                     |
|-----------------------------------------|---------------------|
| <b>Product Color</b>                    | White               |
| <b>Product Shipping Dimensions (in)</b> | 15 x 15 x 17        |
| <b>Speed Control Compatible?</b>        | Yes                 |
| <b>Able To Ship Small Parcel</b>        | Yes                 |
| <b>Cfm Range (free Air)</b>             | 1001 - 2500         |
| <b>Cord Length (feet)</b>               | 6                   |
| <b>Fixed Or Portable</b>                | Fixed               |
| <b>Guard Material</b>                   | Powder Coated Steel |
| <b>Oscillating</b>                      | No                  |
| <b>Country Of Origin</b>                | US                  |

|                                 |                                 |
|---------------------------------|---------------------------------|
| <b>Cfm Calculation Standard</b> | ANSI/AMCA<br>Standard<br>230-99 |
|---------------------------------|---------------------------------|

|                               |               |
|-------------------------------|---------------|
| <b>Guard Spacing (inches)</b> | 1/2 - 1 UL507 |
| <b>Cfm/watt (@0.10")</b>      | TBD           |
| <b>Cfm/watt (@0.05")</b>      | TBD           |