

VK24-3

VK24-3

Product Description

Reduce heat stress and improve air quality with Schaefer's uniquely designed circulation fans. Unrivalled in the market, these fans are engineered to produce greater air movement and superior cooling no matter the application. You don't hear them. You don't see them. You only feel them!

Also known as Horizontal Air Flow (HAF) fans, these fans move air in a coherent horizontal pattern creating a gentle 'racetrack' air flow pattern needed in greenhouses to maximize heat distribution and humidity control by mixing the air, from ceiling to floor.

Features

Deep guard design for unmatched performance, low noise levels and safety without sacrificing airflow

Matched high quality motors and blades for maximum efficiency

Powder coated steel guards for increased durability and corrosion resistance

Powder coated steel mounting bracket included

Wide variety of mounting options available for flexible and easy installation

Misting kits available for even greater cooling

Two year warranty

Made in the USA



Specifications

Blade Color	Metallic
Brand	Schaefer
Cfm (free Air)	7750
Rpm 60 Hz Motor	1550-1800
Drive	Direct
Enclosure	TEAO
Frame Size	48
Mount Included	VS24FMT
Phase	3
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	16.3

Diameter (inches)	24
Frequency (hz)	60/50
Guard Color	White
Mount Type Included	Ceiling
Nameplate Amps	1.56 / .78
Number Of Wings	3
Bess Lab Performance Test #	13216
Power (hp)	1/2
Product Net Weight (lbs)	43

Blade Material	Aluminum
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White
Product Shipping Dimensions (in)	27 x 27 x 19
Speed Control Compatible?	No
Cfm Range (free Air)	5001 - 10000
Fixed Or Portable	Fixed
Guard Material	Powder Coated Steel

Cord	Not included
-------------	--------------

Switch	Not included
Voltage	230/460
Maximum Rpm	1734
Air Velocity (@ 5 Times Diameter)	1320

Oscillating	No
Rpm 50 Hz Motor	1350-1500
Country Of Origin	US
Guard Spacing (inches)	1/2 - 1 UL507