



VKM36-O

VKM36-O

Product Description

Tired of continually replacing your mobile drum fans? Schaefer mobile drum fans have "Schaefer-Tough" polyethylene housing and durable reinforced galvanized steel wheel carriage for impact and rust resistance. These fans are built to last, the best looking fans in the industry and move massive amounts of air at high velocities. A single "Schaefer-Tough" mobile fan will not only take the place of several lower performance fans, but out live them as well, lasting for 10+ years.

Features

High-density polyethylene housing for superior impact, abrasion and temperature-cracking resistance

Galvanized steel base for complete corrosion resistance inside and out

Narrow fan profile, and ergonomic pull and base handles for easy portability

Large rubber wheels mounted inside the fan profile for convenience and safety

Stacking tabs for storage and transportation savings included on OSHA VKM models, optional on others

OSHA compliant guard

Two year warranty

Made in the USA



Specifications

Blade Color	Gray
Brand	Schaefer
Cfm (free Air)	11020
Rpm 60 Hz Motor	800-900
Drive	Direct
Enclosure	TEAO
Frame Size	48Y
Housing Material	Polyethylene
Phase	1
Speeds	1
Vfd Compatible	No
Cfm/watt (free Air)	25.1

Frequency (hz)	60
Guard Color	White
Nameplate Amps	7/3.5
Number Of Wings	3
Bess Lab Performance Test #	13212
Power (hp)	1/2
Product Net Weight (lbs)	85
Switch	On cord
Voltage	115/230 & 110/220
Maximum Rpm	825

Product Shipping Dimensions (in)	43 x 41 x 21
Able To Ship Small Parcel	No
Cfm Range (free Air)	10001 - 15000
Cord Length (feet)	12
Fixed Or Portable	Portable
Guard Material	Powder Coated Steel
Oscillating	No
Product Certifications	CSA
Rpm 50 Hz	700-800

Cord	Included - Wired
Diameter (inches)	36

Air Velocity (@ 5 Times Diameter)	610
Blade Material	Galvanized Steel
Cfm Calculation Standard	ANSI/AMCA Standard 230-99
Product Color	White

Motor	
Country Of Origin	US
Guard Spacing (inches)	1/2 OSHA
Housing Color	White