

ZP14K6E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	50	Displacement (in ³ /Rev):	.88
Condensing Temp. (°F)	130.00	100	Displacement (ft ³ /Hr):	
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.56
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.56
Capacity (BTU/hr)	14700	20200	Overall Height (in):	14.94
Power (W):	1505	962	Mounting Length (in):	7.50
Current (Amps):	6.65	4.25	Mounting Width (in):	7.50
EER(BTU/Wh):	9.75	21.05	Mounting Height (in):	15.96
Mass Flow (lbs/hr):	216	248	Suction Size (in),Type:	3 / 4 Stub
Sound Data @ 50 / 115			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	66 Avg	71 Max	Initial Oil Charge (oz):	21
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	17
Record Date:	2017-04-24		Oil Type:	3MA
			Net Weight (lbs):	44.3
			Internal Free Volume (in ³):	134.0
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors					
		Type	Part No	Low MFD	High MFD	Volt s	User Description
LRA High* (Amps):	47.5						
LRA Low*(Amps):	47.5	Run Capacitor	014-0064-06	30.0	0.0	370	
LRA Half Winding (Amps):							
MCC (Amps):	14	Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL
Max Operating Current (Amps):	11.0						
RLA, MCC/1.4(use for contactor selection)(Amps):	10.0						
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	9.0						
RPM:	3500						
Box IP :	21						
UL File No:	SA2337						
UL File Date:	2003-12-16						

*Low and High refer to the low and high nominal voltage ranges for

which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
-------------	---------	-------	-----------	-------------