

ZP38K5E-TF5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V , [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	50	Displacement (in^3/Rev):	2.18	
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):		
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.56	
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.56	
Capacity (BTU/hr)	38000	51600	Overall Height (in):	16.94	
Power (W):	3600	2370	Mounting Length (in):	7.50	
Current (Amps):	10.3	7.35	Mounting Width (in):	7.50	
EER(BTU/Wh):	10.55	21.8	Mounting Height (in):	17.17	
Mass Flow (lbs/hr):	560	635	Suction Size (in),Type:	7 / 8 Stub	
Sound Data @ 45 / 130			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	71 Avg	76 Max	Initial Oil Charge (oz):	42	
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	36	
Record Date:	2017-03-01		Oil Type:	3MA	
			Net Weight (lbs):	67.0	
			Internal Free Volume (in^3):	209.5	
			Horse Power:	*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors				
LRA High* (Amps):	83.1	Type	Part No	Low MFD	High MFD	Volts User Description
LRA Low*(Amps):		No data available in table				
LRA Half Winding (Amps):						
MCC (Amps):	21.2					
Max Operating Current (Amps):	14.0					
RLA, MCC/1.4(use for contactor selection)(Amps):	15.1					
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	13.6					
RPM:	3500					
Box IP :	21					
UL File No:	SA-2337					
UL File Date:	2003-12-17					

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Alternate Applications				
Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/220	3	50	Air Conditioning