

ZPS31K5E-PFV

HFC, R-410A, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical	
Evaporator Temp. (°F)	45.00	50	Displacement (in ³ /Rev):	1.84
Condensing Temp. (°F)	130.00	115	Displacement (ft ³ /Hr):	223.1
Return Gas Temp. (°F)	65.00	70	Overall Length (in):	9.56
Liquid Temp. (°F)	115.00	100	Overall Width (in):	9.56
Capacity (BTU/hr)	31500	39000	Overall Height (in):	15.27
Power (W):	3060	2510	Mounting Length (in):	7.50
Current (Amps):	13.6	11.15	Mounting Width (in):	7.50
EER(BTU/Wh):	10.3	15.55	Mounting Height (in):	16.02
Mass Flow (lbs/hr):	464	520	Suction Size (in),Type:	3 / 4 Stub
Sound Data @ 45 / 130			Discharge Size (in),Type:	1 / 2 Stub
Sound Power (dBA):	68 Avg	73 Max	Initial Oil Charge (oz):	25
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	21
Record Date:	2017-03-22		Oil Type:	3MA
			Net Weight (lbs):	49.6
			Internal Free Volume (in ³):	115.7
			Horse Power:	
			*Overall compressor height on Copeland Brand Product's specified mounting grommets.	

Electrical		Capacitors					
		Type	Part No	Low MFD	High MFD	Volt s	User Description
LRA High* (Amps):	83.0						
LRA Low*(Amps):		Run Capacitor	014-0064-08	40.0	0.0	370	
LRA Half Winding (Amps):							
MCC (Amps):	25.1	Start Capacitor	014-0061-27	88.0	106.0	330	OPTIONAL
Max Operating Current (Amps):	23.0						
RLA, MCC/1.4(use for contactor selection)(Amps):	17.9						
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	16.1						
RPM:	3500						
Box IP :	21						
UL File No:	SA2337						
UL File Date:	2003-12-16						

*Low and High refer to the low and high nominal voltage ranges for

which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	208/230	1	60	A/C, 67% Load Of Compressor Model
