HFC, R-407C, 60 Hz, 3 - Phase, 200/230 V , Also Available with Variable Frequency Drives

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	5.68	
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):		
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	9.69	
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69	
Capacity (BTU/hr)	68600	82000	Overall Height (in):	17.75	
Power (W):	6040	4270	Mounting Length (in):	7.50	
Current (Amps):	17.55	13.75	Mounting Width (in):	7.50	
EER(BTU/Wh):	11.35	19.2	Mounting Height (in):	18.00	
Mass Flow (lbs/hr):	991	1010	Suction Size (in),Type:	7 / 8 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	75 Avg	80 Max	Initial Oil Charge (oz):	60	
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	56	
Record Date:	2014-08-05		Oil Type:	ЗМА	
			Net Weight (lbs):	86.0	
			Internal Free Volume (in^3):	362.0	
			Horse Power:	5.5	
			*Overall compressor height on Copeland Brand F mounting grommets.	roduct's specified	
Electrical			Capacitors		
LRA High* (Amps):		156.0	Type Part No Low MFD High MFD Volts	User Description	
LRA Low*(Amps):			No data available in table		
LRA Half Winding (Amps):					
MCC (Amps):		29			
Max Operating Current (Amps):		25.0			
RLA, MCC/1.4(use for contactor selection)(Amps):		20.7			
RLA, MCC/1.56(use for breaker & mp; wire size selection)(Amps):		18.6			
RPM:		3500			
Box IP:		21			
UL File No:		SA-2337			
UL File Date:		1993-07- 26			
*Low and High refer to the low and high nominal voltage ranges for					

which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	200/220	3	50	Air Conditioning
R-22 HCFC	200/230	3	60	Air Conditioning
R-407C HFC	200/220	3	50	Air Conditioning