ZR72KCE-TFD

HFC, R-407C, 60 Hz, 3 - Phase, 460 V , Also Available with Variable Frequency Drives

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Performance			Mechanical		
Evaporator Temp. (°F)	45.00	45	Displacement (in^3/Rev):	5.98	
Condensing Temp. (°F)	130.00	100	Displacement (ft^3/Hr):		
Return Gas Temp. (°F)	65.00	65	Overall Length (in):	9.69	
Liquid Temp. (°F)	115.00	85	Overall Width (in):	9.69	
Capacity (BTU/hr)	72300	86800	Overall Height (in):	17.75	
Power (W):	6420	4400	Mounting Length (in):	7.50	
Current (Amps):	9.45	7.2	Mounting Width (in):	7.50	
EER(BTU/Wh):	11.25	19.75	Mounting Height (in):	18.00	
Mass Flow (Ibs/hr):	1045	1070	Suction Size (in),Type:	7 / 8 Stub	
Sound Data @			Discharge Size (in),Type:	1 / 2 Stub	
Sound Power (dBA):	75 Avg	80 Max	Initial Oil Charge (oz):	60	
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	Oil Recharge (oz):	56	
Record Date:	2014-08-05		Oil Type:	ЗМА	
			Net Weight (Ibs):	85.0	
			Internal Free Volume (in^3):	248.0	
			Horse Power:	6.0	
			*Overall compressor height on Copeland Brand Pro mounting grommets.	duct's specified	
Electrical			Capacitors		
LRA High* (Amps):		75.0	Type Part No Low MFD High MFD Volts Us	er Description	
LRA Low*(Amps):			No data available in table		
LRA Half Winding (Amps):					
MCC (Amps):		14			
Max Operating Current (Amps):		12.1			
RLA, MCC/1.4(use for contactor selection)(Amps):		10.0			
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):		9.0			
RPM:		3500			
Box IP :		21			
UL File No:		SA-2337			
UL File Date:		1993-07- 26			

*Low and High refer to the low and high nominal voltage ranges for

which the motor is approved.

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-134a HFC	460	3	60	Air Conditioning
R-134a HFC	380/420	3	50	Air Conditioning
R-22 HCFC	460	3	60	Air Conditioning
R-22 HCFC	380/420	3	50	Air Conditioning
R-407C HFC	380/420	3	50	Air Conditioning